
SAMSUNG

A BRIGHT IDEA FOR YOUR BOTTOM LINE



L-TUBE SERIES										
Family	PERFORMER*	PERFORMER*	PERFORMER*	PERFORMER*	PERFORMER*	PERFORMER*	ESSENTIAL*	ESSENTIAL*	ESSENTIAL*	
Size	2 ft.	2 ft.	2 ft.	4 ft.						
Power Consumption (W)	9.5	9.5	9.5	18	18	18	16.5	16.5	16.5	
Efficacy (Lm/W)	100	105.3	110.5	113.9	116.7	119.4	100.6	106.7	109.8	
Lumens	950	1,000	1,050	2,050	2,100	2,150	1,650	1,750	1,800	
CCT (K)	3,500	4,000	5,000	3,500	4,000	5,000	3,000	4,000	5,000	
Lifetime (hours)	50,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000	
CRI	83	83	85	83	83	85	83	83	85	
Dimmable	No									

















Applications: Office, Parking Garage, Industrial, Retail, Hospitality, Cold Storage, and Cove Lighting.



Suitable for general/ambient lighting.

BULB SERIES								
Family	A19	A19	A19*					
Equivalent (W)	40	60	60					
Power Consumption (W)	6.5	11.3	14					
Lumens	500	850	810					
сст (к)	2,700	2,700	2,700					
Efficacy (Lm/W)	76.9	75.2	57.9					
Lifetime (hours)	25,000	25,000	25,000					
CRI	80	80	80					
Dimmable	Yes	Yes	Yes					

^{*} This model is ENERGY STAR® Certified.







6.5W/11.3W A19 Equivalent to 40W/60W







Applications: Residential, Office, Hospitality, Restaurant, Bar, and Cafe. (Suitable for general/ambient lighting.)







Applications: Residential, Hospitality, and Restaurant. (Suitable for decorative lighting and chandeliers.)

DECORATIVE SERIES										
Family	Candle*	Candle*	Candle	Candle						
Equivalent (W)	25	25	40	40						
Power Consumption (W)	3.2	3.2	5.2	5.2						
Lumens	160	160	300	300						
CCT (K)	2,700	2,700	2,700	2,700						
Efficacy (Lm/W)	53.3	53.3	60.0	60.0						
Lifetime (hours)	15,000	15,000	20,000	20,000						
CRI	80	80	80	80						
Dimmable	Yes	Yes	Yes	Yes						

^{*} These models are ENERGY STAR® Certified.



3.2W/5.2W CANDLE Equivalent to 25W/40W



3.2W/5.2W CANDLE Equivalent to 25W/40W

PAR SERIES																		
Family	PAR20	PAR20	PAR20	PAR20	PAR30*	PAR30*	PAR30*	PAR30*	PAR30*	PAR30*	PAR30 LN*	PAR30 LN*	PAR30 LN*	PAR30 LN*	PAR30 LN*	PAR30 LN*	PAR38	PAR38
Equivalent (W)	50	50	50	50	75	75	75	75	75	75	75	75	75	75	75	75	85	85
Power Consumption (W)	7.6	7.6	7.6	7.6	15	15	15	15	15	15	15	15	15	15	15	15	19	19
Lumens	500	500	550	550	930	930	800	800	960	960	930	930	800	800	960	960	1,440	1,440
CCT(K)	2,700	2,700	3,000	3,000	2,700	2,700	2,700	2,700	3,000	3,000	2,700	2,700	2,700	2,700	3,000	3,000	3,000	3,000
Beam Angle	25	36	25	36	25	40	25	40	25	40	25	40	25	40	25	40	25	40
СВСР	1,600	900	1,600	900	3,910	1,700	3,190	1,400	4,040	1,770	3,900	1,700	3,190	1,400	4,040	1,700	4,000	2,500
Lifetime (hours)	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000	25,000
CRI	80	80	80	80	80	80	94	94	80	80	80	80	94	94	80	80	80	80
Dimmable	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes										

^{*} These models are ENERGY STAR® Certified.



7.6W PAR20 Equivalent to 50W



15W PAR30 Equivalent to 75W



15W PAR30 LN Equivalent to 75W



19W PAR38 Equivalent to 85W



Applications: Retail, Hospitality, Office, Museum, and Restaurant. (Suitable for accent lighting.)

BR SERIES									
Family	BR30*	BR40*	BR40*						
Equivalent (W)	65	90	90						
Power Consumption (W)	10	15.5	15.5						
Lumens	700	990	990						
сст (к)	2,700	3,000	2,700						
Efficacy (Lm/W)	70	63.9	63.9						
Lifetime (hours)	25,000	25,000	25,000						
CRI	80	80	80						
Dimmable	Yes	Yes	Yes						

^{*} These models are ENERGY STAR® Certified.



10W BR30 Equivalent to 65W



15.5W BR40 Equivalent to 90W







Applications: Residential, Hospitality, Restaurant, and Office. (Suitable for general/ambient lighting.)







 $\label{lem:continuous} Applications: Residential, Hospitality, Office, Museum, and Restaurant.$ (Suitable for accent lighting.)

MR16 SERIES										
Family	MR16	MR16	MR16	MR16	MR16					
Equivalent (W)	35	35	35	35	20					
Power Consumption (W)	7	7	7	7	4					
Lumens	350	350	400	400	210					
сст (к)	2,700	2,700	3,000	3,000	2,700					
Beam Angle	25	40	25	40	40					
СВСР	1470	680	1560	720	420					
Lifetime (hours)	25,000	25,000	25,000	25,000	15,000					
CRI	80	80	80	80	80					
Dimmable	Yes	Yes	Yes	Yes	No					



7W MR16 GU5.3 Equivalent to 35W



4W MR16 GU10 Equivalent to 20W

SAMSUNG

1ST TO MARKET WITH LED TV



#1 IN SEMICONDUCTOR TECHNOLOGY



HIGH-PERFORMANCE LED LIGHTING PORTFOLIO







