

LED Glass T8 Hybrid Tubes

DIMENSIONS



APPLICATION

The LHT8 features a dual mode internal driver that automatically adapts to either ballasted fixtures or direct AC voltage formats. Simply plug it in and turn it on for energy savings over 40 percent! The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution. The LT8 family of LED T8 lamps combine high-performance LEDs, highly-engineered optics to traditional T8 lamp form factors to bring you the most advanced line of LED T8 Lamps on the market. Multiple lumen packages mean there is an LT8 that is just right for your lighting needs.

FEATURES

- Instant Start
- Universal Voltage: 120-277V
- 50,000 Hour Life
- Mercury Free and Virtually no UV or IR Light
- Easily Retrofit into most common linear fluorescent fixtures
- Hybrid Tube: Compatible with most Electronic & Magnetic Ballasts & Direct Voltage Compatible
- Direct voltage format works on any two pin combination which greatly simplifies the rewiring process

LISTING

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards.

WARRANTY

5-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

ORDERING INFORMATION

Example Model Number: LHT8-18-840-F

SERIES	WATTAGE	COLOR TEMPERATURE	LENS
LHT8	15	840	FC
	10- (10W, 1400 Lumens, 24") ¹ 12- (12W, 1800 Lumens, 48") ¹ 15- (15W, 2200 Lumens, 48")	835 - 80 CRI; 3500 Kelvin 840 - 80 CRI; 4000 Kelvin 850 - 80 CRI; 5000 Kelvin	FC- Frosted Lens

Notes:

¹Made to order items. Minimum 90 day lead time. Minimum 500 order quantity