

LED AREA LIGHTS



FEATURES


- Well suited light distribution for parking lot and roadway lighting.
- Advanced heat sink design makes fixture light in weight and better at heat dissipation
- Installation angle -90 ~ +90° adjustable.
- Beautiful appearance, using CREE LED chips and high quality driver.
- IP65 Rated.
- DLC and UL Listed




50% ENERGY EFFICIENCY & LONG LIFE
60% MORE ENERGY EFFICIENT THAN STANDARD HID LAMPS
TYPICAL PAYBACK OF 1 - 3 YEARS

SKU #	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-10827	5000	16,500	N/A	150	120-277	YES	SLIP FITTER	70,000	5 years

ADDITIONAL PHOTOS



Type III



FEATURES

- Longer life span than Metal Halide
- Minimizes Maintenance Checks
- Type III light distribution

TYPICAL APPLICATIONS

- Security Lighting
- Pedestrian Lighting

WARRANTY

WARRANTY **5 Years**

SPECIFICATIONS

PERFORMANCE

Cree LED Chip
16500 Lumen Output (IES)
150W Power Consumption
120 lm/W Efficacy (IES)
5000K Color Temperature
N/A CRI
>50,000 hrs Lumen Maintenance
100-277 Input Voltage
150W Power Factor

ENVIRONMENTAL

IP65 IP Rating
-40~+45°C Operating Temperature
-40~+80°C Storing Temperature
10%-95% Humidity

PHYSICAL

Dimensions (533.26 x 330 x 65mm)
9.97kg Weight
Slip Fitter Mounting Options
Fixture Material Die-Casting Aluminum



PHOTOMETRICS NON-SHADED