

F32T8/SPX50/ECO2



68853

88.7
lumens/watt

F32T8/SPX50/ECO2

Specifications

GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	2.95 mg
Mercury-Picogrm per mean lm hr	35.7
Rated Life Instant Start-Hrs	21000 h @ 3 h 30000 h @ 12 h
Rated Life Rapid Start - Hrs	30000 h @ 3 h 36000 h @ 12 h
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Sodalime glass
Rated Life Hours-nominal	30000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	32 W
---------------------	------

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2725 lm
Nominal Initial Lumen per Watt	88.7
Initial Lumens-nominal	2900 lm
Color Rendering Index-CRI	80
Color Temperature	5000 K

DIMENSIONS

Diameter	1.0 in
Nominal Length	48.0 in

PACKAGING INFORMATION

Alternative Unit Of Measure	CASE
Standard Package Quantity	36
Ean UPC	043168688536
Standard Package GTIN	10043168688533
Length	48.81 in
Width	7.88 in
Height	7.31 in
Volume	1.62708 cuft
Gross Weight	20.0 lb
Pack Level Description	Case
Sales Unit	Case
UCC	043168688536