

PRODUCT FOCUS

HIGH MOUNT AREA LIGHT

Outdoor Fixture



SK4HM651AC
10,000 Hour*
(7) 6762711553 (0)*



ML65ALRLDL
10,000 Hour*
(7) 6762711720 (6)*



ML85ALRLDL
10,000 Hour*
(7) 6762711726 (8)



ML4HM651ACARMST
ACCESSORY
(7) 6762712669 (7)*

* UPC Codes

*Included with purchase

HIGH MOUNT AREA LIGHT SPECIFICATIONS

Order Code	Description	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W"xMOL")
72118	SK4HM651AC	10,000	Box	1	9.5" x 16.5"

HIGH MOUNT AREA LIGHT ACCESSORIES

Order Code	Description	Dimensions (Dia."xL")
71275	ML4HM651ACARMST - Arm for Area Light	1.5" x 19"

REPLACEMENT LAMP SPECIFICATIONS

Order Code	Watts	Description	Mercury Vapor Equivalent	Lumens	Efficacy (lm/W)	Power Factor	Lamp Life (Hrs)	Pack Case	Case Pack	Dimensions (W"xMOL")	CCT
70217	65	ML65ALRLDL (Included)	Box	4350	70	.5	10,000	Box	6	3.5" x 11.9"	5000
70415	85	ML85ALRLDL	250	5700	67	.5	10,000	Box	6	3.5" x 11"	5000
70414	85	ML85ALRLDL	250	5700	67	.5	10,000	Box	6	3.5" x 11"	2800

SPECIAL NOTES	LOCATIONS	LOCATIONS
<ul style="list-style-type: none"> >> 65 Watt and 85 Watt Area Replacement Lamps available >> 1 Year warranty from date of purchase 	<ul style="list-style-type: none"> • Driveways • Work Areas 	<ul style="list-style-type: none"> • Yards • Parking Lots • Barns • Garages • Sheds • Utility Poles

BENEFITS	SPECIFICATIONS
<ul style="list-style-type: none"> • Free twist & lock photo cell - Dusk to Dawn • Long Life - 10,000 Hours • UL Certified • Self Ballasted Lamp • Instant Start 	<ul style="list-style-type: none"> • Ballast Type >> Electronic • Starting Method >> Instant Start • Input Line Voltage >> 120VAC • Input Line Frequency >> 50/60HZ • Operating Temperature >> 0°-100°F • Color Rendering Index >> 84

All specifications are subject to change without notice. *HPF: High Power Factor *NPF: Nominal Power Factor
Contains Mercury Hg Dispose of according to Local, State, and Federal Law / www.lamprecycle.org