TECHNICAL DATA SHEET



FEATURES

- **DIRECT WIRE OR PLUG & GO™** Simple rewiring installation allows lamps to run on the main or use it with a magnetic ballast as a plug and go.
- Exceptional efficacy.
- Universal voltage using direct wire.

APPLICATION

Replaces CFL PL Lamps with G23/2 Pin base frequently used in downlights and sconces.

20185 LED 180° PL HYBRID

TWO PIN-BASE REPLACEMENT LAMPS FOR CFLS

PRODUCT DETAILS

ELECTRICAL	
Wattage	4.5W
Voltage	120-277V
Current	40mA
Power Factor	N/A
Total Harmonic Distortion (THD)	N/A
LIGHTING PERFORMANCE	
Lumens	450
Lumens Per Watt (Lm/W)	100
Color Temperature (CCT)	4000K
Color Rendering (CRI)	83
Beam Angle	180°
Light Distribution	N/A
Dimmable Lighting Control	NOT DIMM Q BLE
ENVIRONMENT	
Operating Temperature	-20°C ~ 45°C
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Style	Open
CERTIFICATIONS	

LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	N/A		
CONSTRUCTION			
Housing	Aluminum / PC		
Base / Power Supply	G23 2 Pin / Plug In		
Finish	White		
PACKAGING			
Master Carton	20pc / 10899645001209		
Individual Box	899645001202		
Country of Origin	China		
HS Tariff	9405.40.8200		
DIMENSIONS			
Dimensions (Inches)	6.5"(L) x 1.3"(W) x 0.8"(H)		
6.5"	— 0.8"		
I	1.3"		



ORDERING

ITEM# [DESCRIPTION	CASE
20185	LED 4.5WPL/180°/FR/40K/G23/2 PIN/120-277V HYBRID	20