TECHNICAL DATA SHEET



FEATURES

• **DIRECT WIRE OR PLUG & GO[™]** - Simple rewiring installation allows lamps to run on the main or use it with a magnetic ballast as a plug and go.

- Exceptional efficacy.
- Universal voltage using direct wire.

APPLICATION

Replaces CFL PL Lamps with G23/2 Pin base frequently used in downlights and sconces.

20186 LED 180° PL HYBRID

TWO PIN-BASE REPLACEMENT LAMPS FOR CFLS

PRODUCT DETAILS

ELECTRICAL	
Wattage	4.5W
Voltage	120-277V
Current	40mA
Power Factor	N/A
Total Harmonic Distortion (THD)	N/A
LIGHTING PERFORMANCE	
Lumens	450
Lumens Per Watt (Lm/W)	100
Color Temperature (CCT)	5000K
Color Rendering (CRI)	83
Beam Angle	180°
Light Distribution	N/A
Dimmable Lighting Control	NOT DIMMABLE
ENVIRONMENT	
Operating Temperature	-20°C ~ 45°C
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Style	Open
CERTIFICATIONS	

LIFESPAN	
Average Life (Hours)	50,000
Warranty (Years)	5
COMPONENTS	
LED Light Source	N/A
CONSTRUCTION	
Housing	Aluminum / PC
Base / Power Supply	G23 2 Pin / Plug In
Finish	White
PACKAGING	
Master Carton	20pc / 10899645001759
Individual Box	899645001752
Country of Origin	China
HS Tariff	9405.40.8200
DIMENSIONS	
Dimensions (Inches)	6.5"(L) x 1.3"(W) x 0.8"(H)
6.5" —	0.8"

1.3"



ORDERING

ITEM#	DESCRIPTION	CASE
20186	LED 4.5WPL/180°/FR/50K/G23/2 PIN/120-277V HYBRID	20

Ш

Published lumens on LED products are approximate and may vary slightly.