

# FLF15 / **FLF30** / FLF50



## Flood lights

This series has a thin, smart and stylish shape with excellent cooling and high lumen efficacy of 115-120 lm/w. With various mounting options, this series is a great choice for anyone needing large amounts of light at a energy saving cost.

### Features

- Corrosion-Resistant Coating Finish
- Imported high-dense aluminum alloy housing
- High transparency and weather resistant lens
- Color options: **Bronze**, Black, White, Gray

### Applications

- Architecture
- Sports grounds
- Billboards
- High Ways
- Tunnels, Bridges



Installation Diagram

## Specifications

	Model:	FLF15	<b>FLF30</b>	FLF50
General	Lumen Efficacy:	115 lm / w	<b>115 lm / w</b>	120 lm / w
	Lumen Output:	1,725 lm	<b>2,700 lm</b>	6,000 lm
	Input Power:	15W	<b>30W</b>	50W
Electrical	Input Voltage:	100-277V	<b>100-277V</b>	100-277V
	Power Factor:	>90%	<b>&gt;90%</b>	>90%
	Color Temperature (CCT):	3000k - 5700k	3000k - 5700k	3000k - 5700k
Color	Color Rendering Index (CRI):	>80	<b>&gt;80</b>	>80
	Dimmable:	No	<b>No</b>	No
Operational	Dimensions:	Yoke Knuckle 4.66 in x 4.25 in x 1.5 in 6.89 in x 4.76 in x 3.07 in	<b>6.6 in x 6.75 in x 1.6 in</b> 4.72 in x 3.27 in x 2.60 in	7.8 in x 8.5 in x 1.8 in 8.62 in x 5.94 in x 3.54 in
	Rating:	IP65	<b>IP65</b>	IP65
	Warranty:	5 Year	<b>3 Year</b>	5 Year
	Mounting Option:	YK(Yoke)/KN (Knuckle)	<b>YK(Yoke)/KN (Knuckle)</b>	YK(Yoke)/KN (Knuckle)