

Product Specifications



LED Wall Pack

60W LED Wall Pack
EO-WP-60

FEATURES

- System Light Efficacy 81 LPW
- Easy Installation & Maintenance
- IP65
- Five Years Warranty
- ETL
- Optional Shade Included

TYPICAL APPLICATIONS

- Security Lighting
- Pedestrian Lighting

SPECIFICATIONS

PERFORMANCE

LED Chip	OSRAM
Lumen Output (IES)	4,860lm
Power Consumption	60 W
Efficacy (IES)	81 lm/W
Color Temperature	5000K
CRI	≥80
Lumen Maintenance	L70>100,000 hours (Calculated Using TM-21 Calculator)
Input Voltage	100-277 VAC
Power Factor	0.95 minimum

ENVIRONMENTAL

IP Rating	IP65
Operating Temperature	-30 to 45°C (-22 to 113°F)
Storing Temperature	-40 to 80°C (-40 to 167°F)
Humidity	15% to 95% RH

PHYSICAL

Dimensions (L×W×H)	432×230×430 mm (17×9.1×16.3.9 in) (SHADED)
Weight	9.0 kg (19.8 lbs) (SHADED)
Mounting Options	Wall Mount
Fixture Material	Aluminum Alloy


WARRANTY

5 Years




Photometrics

NON SHADED



0.0~180.0




Mounting Hight 3.5m, 0 Tilt, 50LUX-5LUX

Illumination


Height	Light Spot	LUX
3.5m	5x5m	114LUX
4m	7x7m	87LUX
4.5m	8x8m	68LUX
5m	10x10m	55LUX
5.5m	11x11m	46LUX

Beam Angle (50% max)	120 DEG
Luminous Flux (IES)	4,860 lm
Light Efficacy (IES)	81 lm/W
Cutoff Classification	Semi-Cutoff

SHADED



0.0~180.0



Mounting Hight 3.5m, 0 Tilt, 50LUX-5LUX

Illumination

Height	Light Spot	LUX
3.5m	5x5m	114LUX
4m	7x7m	87LUX
4.5m	8x8m	68LUX
5m	10x10m	55LUX
5.5m	11x11m	46LUX

Beam Angle (50% max)	120 DEG
Luminous Flux (IES)	4,620 lm
Light Efficacy (IES)	77 lm/W
Cutoff Classification	Full-Cutoff



Mounting Options

Wall Mount

