



FEATURES

- USA approved LM-80 SMD
- UL DLC LM79 certified
- Input Voltage: 100-277 VAC 50/60Hz
- THD:<20%(at 277V)
- High lumen output, high efficiency, energy saving up to 50%
- Standard Warranty: 5 Years
- Standard Lifetime: Designed to L70 minimum 50,000 hours
- UL# E485624 - DLC# PLTB33D21





50% ENERGY EFFICIENCY & LONG LIFE

TYPICAL PAYBACK OF 1 - 3 YEARS

SKU #	Kelvin	Lumens	Size	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
-------	--------	--------	------	---------	---------	------	----------	------------	----------

LEDF-10164	5000	6250	2X4	50	100-277	YES	CEILING	50000	5 years
-------------------	-------------	-------------	------------	-----------	----------------	------------	----------------	--------------	----------------

ADDITIONAL PHOTOS



FEATURES

- Opaque Lens
- Lightweight design
- LED driver included

TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Office, Conference Rooms
- Hospitals


WARRANTY

Warranty

5 Years

SPECIFICATIONS

Dimmable Yes
 DLC Listed Yes
 Safety Rating UL
 CRI80
 Color..... Stark White
 Color Temperature..... 5000 Kelvin
 Life Hours 50,000
 Wattage 50 Watt
 Lumens..... 6250
 Voltage 100-277
 Finish..... White
 Housing Aluminum
 Mounting Ceiling Grid Mount/Suspended
 Lens Opaque
 Length 47.75 in.
 Height 1.9 in.
 Width 23.7 in.
 Weight 14 lbs.
 Warranty 5 Years



PHOTOMETRICS

