

LED T8 SERIES


BYPass LED T8 - 8FT

COMMERCIAL SPEC GRADE

Replaces 96W 8ft Fluorescent T8



Superior All-Around Light Distribution



Coated Shatter-Resistant Glass



Designed for high efficiency and versatility, the IC-Driver allows for exceptional DIRECT performance



Seamless output from end-to-end, ARCHIPELAGO® Light Engine allows for fully uniform light output



FEATURES

- BYPass the Ballast - Easy Retrofit Installation
- Full Glass Lens with 310° Light Distribution
- Uniform Light Output From End-to-End
- Universal Input Voltage - 120-277V
- Instant-ON with No Flicker
- 5-Year Warranty
- UL Listed

Specifications and Technical Data (T8 | BYPass | 8FT)


MODEL	BASE TYPE	WATTS / EQV.	LUMEN	CCT	LENGTH	VOLTAGE**	CRI	THD	CARTON QTY	LIGHT DISTRIBUTION
LBP8F42	FA8	36W / 96W	4200LM	4100K	8 FT	120-277V	83	<20%	16	310°
LBP8F42	FA8	36W / 96W	4200LM	5000K	8 FT	120-277V	83	<20%	16	310°

* Suitable for use in totally enclosed fixtures

** Suitable for damp locations. Not for use where exposed to the weather or moisture

*** Visit <http://www.archipelagolighting.com/support> for installation instructions

Installation Configuration



Double-Ended Bypass

Light Distribution Curve

