



20235 PLC 4 PIN CFL COMPACT FLUORESCENT

TECHNICAL DATA SHEET


FEATURES

- Light weight and has a low profile
- Excellent color rendition
- Light instantly, no flicker
- Less heat output with a low starting temperature


APPLICATION

Available in a full selection of sizes and designs that allow a convenient fit for nearly every style of fixture. Used for decorative and orientation lighting.

PRODUCT DETAILS

ELECTRICAL	
Wattage	26W
Voltage	120V
LIGHTING PERFORMANCE	
Mean Lumens	1560
Lumens Per Watt (Lm/W)	60
Color Temperature (CCT)	3000K
Color Rendering (CRI)	80
Dimmable Lighting Control	
LIFESPAN	
Average Life (Hours)	12,000
Warranty (Years)	5
CONSTRUCTION	
Housing	Glass / Plastic
Base / Power Supply	G24Q-3
Finish	White
Mercury Content (Hg)	2.2mg

PACKAGING	
Master Carton	200pc / 811768024395
Inner Carton	50pc / N/A
Individual Box	811768024395
Country of Origin	China
HS Tariff	8539.31.0050
DIMENSIONS	
Dimensions (Inches)	6.5"(L) x 1.4"(DIA)



ORDERING

ITEM#	DESCRIPTION	CASE
20235	PLC26/30K/G24Q-3 4 PIN	50/200

Published lumens on products are approximate and may vary slightly.



This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.