



FEATURES

- Integrated powder-coated aluminum heat sink with ground wire
TRIAC dimmable to 5% (forward & reverse phase)
Easy installation with center or screw mounting
Optical grade polycarbonate lens
AC Driver-On-Board technology
On-board line surge protection
12" 18 AWG leads

APPLICATION

- For use in retrofitting flush mounted fixtures at least 6 In. in diameter to LED technology.
Replaces the sockets and bulbs inside flush mount lights
Optional MOV ground surge protection



Table with 10 columns: SKU#, Kelvin, Lumens, Size, Wattage, Voltage, DLC?, Operating Temp, Life Hours, Warranty. Row 1: PLT-50069, 3000, 1350, 6 In., 15, 120, No, -40 to 50° C, 50,000, 5 Years.

SPECIFICATIONS DIMENSIONS

Table with 2 columns: Specification and Value. Rows include DIMMABLE (YES), SAFETY RATING (ETL/UL DAMP LOCATION), COLOR (HALOGEN WHITE), LIFE HOURS (50,000), CRI (80), FINISH (WHITE), HOUSING (ALUMINUM), LENS (POLYCARBONATE), MAX LENS TEMP (176°F), LENGTH (6.06 IN.), WIDTH (6.06 IN.), WEIGHT (1 LB.).

