

# LED Light Engine Retrofit

**PLT**



## FEATURES

- Integrated powder-coated aluminum heat sink with ground wire
- TRIAC dimmable to 5% (forward & reverse phase)
- Easy installation with center or screw mounting
- Optical grade polycarbonate lens
- AC Driver-On-Board technology
- On-board line surge protection
- 12" 18 AWG leads

## APPLICATION

- For use in retrofitting flush mounted fixtures at least 6 In. in diameter to LED technology.
- Replaces the sockets and bulbs inside flush mount lights

❖ Optional MOV ground surge protection



SKU#	Kelvin	Lumens	Size	Wattage	Voltage	DLC?	Operating Temp	Life Hours	Warranty
PLT-50071	3000	1850	6 In.	22	120	No	-40 to 50° C	50,000	5 Years

## SPECIFICATIONS

DIMMABLE .....	YES
SAFETY RATING .....	ETL/UL DAMP LOCATION
COLOR .....	HALOGEN WHITE
LIFE HOURS .....	50,000
CRI .....	80
FINISH .....	WHITE
HOUSING .....	ALUMINUM
LENS .....	POLYCARBONATE
MAX LENS TEMP.....	176°F
LENGTH .....	6.06 IN.
WIDTH .....	6.06 IN.
WEIGHT .....	1 LB.

## DIMENSIONS

