



RFSF Series

LED Medium Body Strip retrofit with Lens



FEATURES & SPECIFICATIONS

Great Performance Strip Retrofit - now available with Lens. This LED offering is perfect for so many applications.

Designed economically yet with balance and sleek aesthetics. This Kit is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10), or contact factory for more details.

SIZE* (includes strip body)

W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

*All dimensions are inches. Specifications subject to change without notice.

Kit does not include fixture body

2 ft - STANDARD

Example: RFSF24LFRF30W3900LDMV40K

| RFSF | 24L | FR | F30W3900L | DMV | 40K |
|------------------------|----------------|------------------------|---|--------------------------------------|--|
| Series | Length | Lens | Wattage and Lumen | Driver | Kelvin Temperature |
| RFSF | 24L 24" | FR Frosted Lens | F18W2300L 18 System Watts, 2300 Delivered Lumens | DMV 0-10V Dimming 120V - 277V | 30K 3000K |
| Medium Body Strip | | | F24W3000L 24 System Watts, 3000 Delivered Lumens | | 35K 3500K |
| SMRFSF | | | F28W3300L 18 System Watts, 3300 Delivered Lumens | | 40K 4000K |
| Medium Body Strip with | | | F30W3900L 30 System Watts, 3900 Delivered Lumens | | 50K 5000K |
| Microwave Sensor | | | | | |
| | | | | | Options |
| | | | | | WP 6 ft. 3 wire 18 gauge whip |
| | | | | | WP10 6 ft. 4 wire 18 gauge whip |
| | | | | | EM 10w Emergency battery backup |
| | | | | | PI1 3 Wire Harness |
| | | | | | PI3 5 Wire Harness |

*Consult factory for more options



RFSF Series

LED Medium Body Strip retrofit with Lens



4 ft - STANDARD

Example: RFSF48LFRF30W4000LDMV40K

| RFSF | 48L | FR | F30W4000L | DMV | 40K |
|------------------------|---------|-----------------|---|--------------------------------------|--|
| Series | Length | Lens | Wattage and Lumen | Driver | Kelvin Temperature |
| RFSF | 48L 48" | FR Frosted Lens | F24W3200L 24 System Watts, 3200 Delivered Lumens | DMV 0-10V Dimming 120V - 277V | 30K 3000K |
| Medium Body Strip | | | F30W4000L 30 System Watts, 4000 Delivered Lumens | | 35K 3500K |
| SMRFSF | | | F35W4500L 35 System Watts, 4500 Delivered Lumens | | 40K 4000K |
| Medium Body Strip with | | | F48W6000L 48 System Watts, 6000 Delivered Lumens | | 50K 5000K |
| Microwave Sensor | | | F57W7100L 57 System Watts, 7100 Delivered Lumens | | |
| | | | | | Options |
| | | | | | WP 6 ft. 3 wire 18 gauge whip |
| | | | | | WP10 6 ft. 4 wire 18 gauge whip |
| | | | | | EM 10w Emergency battery backup |
| | | | | | PI1 3 Wire Harness |
| | | | | | PI3 5 Wire Harness |

8 ft - STANDARD

| RFSF | FR | 96L | F96W9600L | DMV | 30K |
|------------------------|-----------------|---------|---|--------------------------------------|--|
| Series | Lens | Length | Wattage and Lumen | Driver | Kelvin Temperature |
| RFSF | FR Frosted Lens | 96L 96" | F48W6000L 48 System Watts, 6000 Delivered Lumens | DMV 0-10V Dimming 120V - 277V | 30K 3000K |
| Medium Body Strip | | | F57W7100L 57 System Watts, 7100 Delivered Lumens | | 35K 3500K |
| SMRFSF | | | F70W9100L 70 System Watts, 9100 Delivered Lumens | | 40K 4000K |
| Medium Body Strip with | | | F96W9600L 96 System Watts, 9600 Delivered Lumens | | 50K 5000K |
| Microwave Sensor | | | F118W14200L 118 System Watts, 14200 Delivered Lumens | | |
| | | | | | Options |
| | | | | | WP 6 ft. 3 wire 18 gauge whip |
| | | | | | WP10 6 ft. 4 wire 18 gauge whip |
| | | | | | EM 10w Emergency battery backup |
| | | | | | PI1 3 Wire Harness |
| | | | | | PI3 5 Wire Harness |

*Consult factory for more options