



# RFSF Series

## LED Medium Body Strip retrofit with Lens



### FEATURES & SPECIFICATIONS

Great Performance Strip Retrofit - now available with Lens. This LED offering is perfect for so many applications.

Designed economically yet with balance and sleek aesthetics. This Kit is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed.

### MOUNTING

Surface mount, chain hung, double stem.

### TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10), or contact factory for more details.

#### SIZE\* (includes strip body)

##### W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

\*All dimensions are inches. Specifications subject to change without notice.

\*\*Kit does not include fixture body\*\*

### 2 ft - STANDARD

Example: RFSF24LFRF30W3900LDMV40K

RFSF	24L	FR	F30W3900L	DMV	40K
Series	Length	Lens	Wattage and Lumen	Driver	Kelvin Temperature
<b>RFSF</b>	<b>24L</b> 24"	<b>FR</b> Frosted Lens	<b>F18W2300L</b> 18 System Watts, 2300 Delivered Lumens	<b>DMV</b> 0-10V Dimming 120V - 277V	<b>30K</b> 3000K
Medium Body Strip			<b>F24W3000L</b> 24 System Watts, 3000 Delivered Lumens		<b>35K</b> 3500K
<b>SMRFSF</b>			<b>F28W3300L</b> 18 System Watts, 3300 Delivered Lumens		<b>40K</b> 4000K
Medium Body Strip with			<b>F30W3900L</b> 30 System Watts, 3900 Delivered Lumens		<b>50K</b> 5000K
Microwave Sensor					
					<b>Options</b>
					<b>WP</b> 6 ft. 3 wire 18 gauge whip
					<b>WP10</b> 6 ft. 4 wire 18 gauge whip
					<b>EM</b> 10w Emergency battery backup
					<b>PI1</b> 3 Wire Harness
					<b>PI3</b> 5 Wire Harness

\*Consult factory for more options



# RFSF Series

## LED Medium Body Strip retrofit with Lens



### 4 ft - STANDARD

Example: RFSF48LFRF30W4000LDMV40K

Series	Length	Lens	Wattage and Lumen	Driver	Kelvin Temperature	Options
<b>RFSF</b>	<b>48L</b> 48"	<b>FR</b> Frosted Lens	<b>F24W3200L</b> 24 System Watts, 3200 Delivered Lumens	<b>DMV</b> 0-10V Dimming 120V - 277V	<b>30K</b> 3000K	
Medium Body Strip			<b>F30W4000L</b> 30 System Watts, 4000 Delivered Lumens		<b>35K</b> 3500K	
<b>SMRFSF</b>			<b>F35W4500L</b> 35 System Watts, 4500 Delivered Lumens		<b>40K</b> 4000K	
Medium Body Strip with Microware Sensor			<b>F48W6000L</b> 48 System Watts, 6000 Delivered Lumens		<b>50K</b> 5000K	
			<b>F57W7100L</b> 57 System Watts, 7100 Delivered Lumens			
						<b>WP</b> 6 ft. 3 wire 18 gauge whip
						<b>WP10</b> 6 ft. 4 wire 18 gauge whip
						<b>EM</b> 10w Emergency battery backup
						<b>PI1</b> 3 Wire Harness
						<b>PI3</b> 5 Wire Harness

### 8 ft - STANDARD

Series	Lens	Length	Wattage and Lumen	Driver	Kelvin Temperature	Options
<b>RFSF</b>	<b>FR</b> Frosted Lens	<b>96L</b> 96"	<b>F48W6000L</b> 48 System Watts, 6000 Delivered Lumens	<b>DMV</b> 0-10V Dimming 120V - 277V	<b>30K</b> 3000K	
Medium Body Strip			<b>F57W7100L</b> 57 System Watts, 7100 Delivered Lumens		<b>35K</b> 3500K	
<b>SMRFSF</b>			<b>F70W9100L</b> 70 System Watts, 9100 Delivered Lumens		<b>40K</b> 4000K	
Medium Body Strip with Microware Sensor			<b>F96W9600L</b> 96 System Watts, 9600 Delivered Lumens		<b>50K</b> 5000K	
			<b>F118W14200L</b> 118 System Watts, 14200 Delivered Lumens			
						<b>WP</b> 6 ft. 3 wire 18 gauge whip
						<b>WP10</b> 6 ft. 4 wire 18 gauge whip
						<b>EM</b> 10w Emergency battery backup
						<b>PI1</b> 3 Wire Harness
						<b>PI3</b> 5 Wire Harness

\*Consult factory for more options