



RFSF Series

LED Medium Body Strip retrofit with Lens



FEATURES & SPECIFICATIONS

Great Performance Strip Retrofit - now available with Lens. This LED offering is perfect for so many applications.

Designed economically yet with balance and sleek aesthetics. This Kit is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10), or contact factory for more details.

SIZE* (includes strip body)

W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

*All dimensions are inches. Specifications subject to change without notice.

Kit does not include fixture body

2 ft - STANDARD

Example: RFSF24LFRF30W3900LDMV40K

RFSF	24L	FR	F30W3900L	DMV	40K
Series	Length	Lens	Wattage and Lumen	Driver	Kelvin Temperature
RFSF	24L 24"	FR Frosted Lens	F18W2300L 18 System Watts, 2300 Delivered Lumens	DMV 0-10V Dimming 120V - 277V	30K 3000K
Medium Body Strip			F24W3000L 24 System Watts, 3000 Delivered Lumens		35K 3500K
SMRFSF			F28W3300L 18 System Watts, 3300 Delivered Lumens		40K 4000K
Medium Body Strip with			F30W3900L 30 System Watts, 3900 Delivered Lumens		50K 5000K
Microwave Sensor					
					Options
					WP 6 ft. 3 wire 18 gauge whip
					WP10 6 ft. 4 wire 18 gauge whip
					EM 10w Emergency battery backup
					PI1 3 Wire Harness
					PI3 5 Wire Harness

*Consult factory for more options



RFSF Series

LED Medium Body Strip retrofit with Lens



4 ft - STANDARD

Example: RFSF48LFRF30W4000LDMV40K

Series	Length	Lens	Wattage and Lumen	Driver	Kelvin Temperature	Options
RFSF	48L 48"	FR Frosted Lens	F24W3200L 24 System Watts, 3200 Delivered Lumens	DMV 0-10V Dimming 120V - 277V	30K 3000K	
Medium Body Strip			F30W4000L 30 System Watts, 4000 Delivered Lumens		35K 3500K	
SMRFSF			F35W4500L 35 System Watts, 4500 Delivered Lumens		40K 4000K	
Medium Body Strip with Microwave Sensor			F48W6000L 48 System Watts, 6000 Delivered Lumens		50K 5000K	
			F57W7100L 57 System Watts, 7100 Delivered Lumens			
						WP 6 ft. 3 wire 18 gauge whip
						WP10 6 ft. 4 wire 18 gauge whip
						EM 10w Emergency battery backup
						PI1 3 Wire Harness
						PI3 5 Wire Harness

8 ft - STANDARD

Series	Lens	Length	Wattage and Lumen	Driver	Kelvin Temperature	Options
RFSF	FR Frosted Lens	96L 96"	F48W6000L 48 System Watts, 6000 Delivered Lumens	DMV 0-10V Dimming 120V - 277V	30K 3000K	
Medium Body Strip			F57W7100L 57 System Watts, 7100 Delivered Lumens		35K 3500K	
SMRFSF			F70W9100L 70 System Watts, 9100 Delivered Lumens		40K 4000K	
Medium Body Strip with Microwave Sensor			F96W9600L 96 System Watts, 9600 Delivered Lumens		50K 5000K	
			HF114W11700L 114 System Watts, 11,700 Delivered Lumens			
						WP 6 ft. 3 wire 18 gauge whip
						WP10 6 ft. 4 wire 18 gauge whip
						EM 10w Emergency battery backup
						PI1 3 Wire Harness
						PI3 5 Wire Harness