



RFSF Series

LED Medium Body Strip retrofit with Lens



FEATURES & SPECIFICATIONS

Great Performance Strip Retrofit - now available with Lens. This LED offering is perfect for so many applications.

Designed economically yet with balance and sleek aesthetics. This Kit is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10), or contact factory for more details.

SIZE* (includes strip body)

W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

*All dimensions are inches. Specifications subject to change without notice.

**Kit does not include fixture body **

2 ft - STANDARD

Example: RFSF24LFRF30W3900LDMV40K

RFSF	24L		FR		F30W3900L		DMV		40K	
Series	Length		Lens		Wattage and Lumen		Driver	Kelvin Temperature		
RFSF	24L	24"	FR	Frosted Lens	F18W2300L	18 System Watts, 2300 Delivered Lumens	DMV	0-10V Dimming 120V - 277V	30K	3000K
Medium Body Strip					F24W3000L	24 System Watts, 3000 Delivered Lumens			35K	3500K
SMRFSF					F28W3300L	18 System Watts, 3300 Delivered Lumens			40K	4000K
Medium Body Strip with					F30W3900L	30 System Watts, 3900 Delivered Lumens			50K	5000K
Microwave Sensor									Options	
									WP	6 ft. 3 wire 18 gauge whip
									WP10	6 ft. 4 wire 18 gauge whip
									EM	10w Emergency battery backup
									PI1	3 Wire Harness
									PI3	5 Wire Harness



RFSF Series

LED Medium Body Strip retrofit with Lens



4 ft - STANDARD

Example: RFSF48LFRF30W4000LDMV40K

RFSF		48L		FR		F30W4000L		DMV		40K		
Series		Length		Lens		Wattage and Lumen		Driver		Kelvin Temperature		
RFSF		48L	48"	FR	Frosted Lens	F24W3200L	24 System Watts, 3200 Delivered Lumens	DMV	0-10V Dimming 120V - 277V	30K	3000K	
Medium Body Strip						F30W4000L	30 System Watts, 4000 Delivered Lumens			35K	3500K	
SMRFSF						F35W4500L	35 System Watts, 4500 Delivered Lumens			40K	4000K	
Medium Body Strip						F48W6000L	48 System Watts, 6000 Delivered Lumens			50K	5000K	
with												
Microwave Sensor						F57W7100L	57 System Watts, 7100 Delivered Lumens					
											Options	
											WP	6 ft. 3 wire 18 gauge whip
											WP10	6 ft. 4 wire 18 gauge whip
											EM	10w Emergency battery backup
											PI1	3 Wire Harness
											PI3	5 Wire Harness

8 ft - STANDARD

RFSF	FR	96L	HF114W11700L	DMV	50K				
Series	Lens		Length		Wattage and Lumen		Driver	Kelvin Temperature	
RFSF	FR	Frosted Lens	96L	96"	F48W6000L	48 System Watts, 6000 Delivered Lumens	DMV	0-10V Dimming 120V - 277V	30K 3000K
Medium Body Strip					F57W7100L	57 System Watts, 7100 Delivered Lumens			35K 3500K
SMRFSF					F70W9100L	70 System Watts, 9100 Delivered Lumens			40K 4000K
Medium Body Strip with Microwave Sensor					F96W9600L	96 System Watts, 9600 Delivered Lumens			50K 5000K
					HF114W14200L	114 System Watts, 11,700 Delivered Lumens			
									Options
									WP 6 ft. 3 wire 18 gauge whip
									WP10 6 ft. 4 wire 18 gauge whip
									EM 10w Emergency battery backup
									PI1 3 Wire Harness
									PI3 5 Wire Harness

*Consult factory for more options