



Catalog Number
Notes
Type

Contractor Select™

FMLRL/FMLS

Low Profile Rounds and Squares LED Flush Mount



With a low-profile, stay-white acrylic diffuser, the FMLRL and FMLS LED flush mounts provide general illumination for residential and light commercial applications such as kitchens, offices, utility work areas and stairways. They are available in 11" and 14" round and 11" square luminaires. Hidden cam-latches provide easy diffuser removal for installation and maintenance. Works with most standard incandescent dimmers.

FEATURES:

- Available in 2 color temperatures; 3000K and 4000K
- Dimmable to 10%
- Long life output eliminates routine maintenance



Catalog Number	UPC	Description	Replaces up to	Lumens	Input Watts	CCT	CRI	VOLTAGE	Pallet qty.
FMLRL 11 14840 M4	753573687405	11" Round LED Flush Mount	75W Incandescent	1,100	16W	4000K	80	120V	120
FMLRL 14 20830 M4	820476883118	14" Round LED Flush Mount	2-60W Incandescent	1,600	24W	3000K	80	120V	72
FMLRL 14 20840 M4	753573687412	14" Round LED Flush Mount	2-60W Incandescent	1,600	24W	4000K	80	120V	72
FMLS 11 14840 M4	753573687436	11" Square LED Flush Mount	75W Incandescent	1,100	16W	4000K	80	120V	120

Accessories: Order as separate catalog number.

DFMLRL11	11" LED low profile round diffuser
DFMLRL14	14" LED low profile round diffuser

Compatible Dimmer Switches

Manufacturer	Part Number(s)	
Leviton	6633P	IPE04
	IPL06	Trimatron 600W
	6674P	
Lutron	DVELV 300P	NTELV 300
	Skylark 300P	NLV 300



Specifications

INTENDED USE:

Provides general illumination in commercial and residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more.

CONSTRUCTION:

Features a white acrylic diffuser and is available in 11" and 14" sizes. Hidden cam-latches provide easy diffuser removal for installation and maintenance.

OPTICS:

11" Round units produce 1100 lumens and 14" Round units produce 1600 lumens, both at 50,000 hours life. 11" Square units produce 1100 lumens at 50,000 hours life.

ELECTRICAL:

Fixture operates at 120 volts, 60 Hz. 11" Standard input = 16 watts, 69 lumens per watt. 14" Standard input = 24 watts, 67 lumens per watt. Works with most standard incandescent dimmers (see list of approved dimmers).

INSTALLATION:

All mounting hardware included.

LISTINGS:

UL Certified to US and Canadian standards and listed suitable for damp locations. ENERGY STAR® certified.

WARRANTY:

5-year limited warranty.

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

Round – FMRL 11

Height: 2-7/8 (7.3)

Width: 11 (27.9)

Round – FMRL 14

Height: 3-1/8 (7.9)

Width: 13-11/16 (34.7)

Square – FMSL 11

Height: 2-7/8 (7.3)

Width: 11 (27.9)

All dimensions are inches (centimeters) unless otherwise indicated.