



Catalog Number
Notes
Type

Contractor Select™

FMLWL LED Wrap

Linear Flush Mount



A low-profile, linear and narrow wraparound with decorative endcaps and a frosted diffuser providing widespread, uniform illumination. Ideal for many applications including corridors, kitchens, breakrooms, utility work areas and stairways.

FEATURES:

- 2' wrap produces 1,200 lumens and 4' produces 2,900 lumens, both at 50,000 hours life
- Operates at 120 volts, 60Hz



Catalog Number	UPC	Description	Lumens	Input Watts	Voltage	Color Temperature	Pallet qty.
FMLWL 24 840	888791197921	2' LED Wrap	1,200	19.6W	120V	4000K	224
FMLWL 48 840	888791197969	4' LED Wrap	2,900	40.77W	120V	4000K	112

Replacement parts	
DFMLWL24	2' white acrylic diffuser
DFMLWL48	4' white acrylic diffuser



Specifications

INTENDED USE:

Provides an LED lighting platform to deliver general ambient lighting for surface-mount ceiling applications. Light engine delivers long life and excellent color to ensure a quality, low-maintenance light installation. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, and more.

CONSTRUCTION:

The LED wrap is constructed of a metal housing with decorative plastic end caps. The white frosted diffuser provides even illumination and softens the appearance of the LEDs for improved aesthetics.

OPTICS:

2' wrap produces 1,200 lumens and 4' produces 2,900 lumens, both at 50,000 hours life. Thermal formed diffuser is of highly transmissive material to minimize lamp image and provides high-angle brightness control. One piece contemporary design wrap around diffuser softens appearance for improved aesthetics.

ELECTRICAL:

Long-life LEDs, coupled with a high-efficiency driver, provide superior illumination for extended service life. 70% LED lumen maintenance at 60,000 hours (L70/60,000). 0-10V dimming driver, dims to 10%.

LISTINGS:

UL certified to US and Canadian standards. Listed for damp locations. Energy Star® certified.

WARRANTY:

5-year limited warranty.

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions


2'

Length: 24-1/2 (62.2)

Width: 5-1/2 (14.0)

Depth: 2-3/5 (6.6)

Weight: 2.5lbs (1.0kg)



4'

Length: 47-2/5 (120.4)

Width: 5-1/2 (14.0)

Depth: 2-3/5 (6.6)

Weight: 5lbs (1.0kg)

All dimensions are inches (centimeters) unless otherwise indicated.