



| |
|----------------|
| Catalog Number |
| Notes |
| Type |

Contractor Select™

FMLWL LED Wrap

Linear Flush Mount



A low-profile, linear and narrow wraparound with decorative endcaps and a frosted diffuser providing widespread, uniform illumination. Ideal for many applications including corridors, kitchens, breakrooms, utility work areas and stairways.

FEATURES:

- 2' wrap produces 1,200 lumens and 4' produces 2,900 lumens, both at 50,000 hours life
- Operates at 120 volts, 60Hz



| Catalog Number | UPC | Description | Lumens | Input Watts | Voltage | Color Temperature | Pallet qty. |
|---------------------|---------------------|--------------------|--------------|---------------|-------------|-------------------|-------------|
| FMLWL 24 840 | 888791197921 | 2' LED Wrap | 1,200 | 19.6W | 120V | 4000K | 224 |
| FMLWL 48 840 | 888791197969 | 4' LED Wrap | 2,900 | 40.77W | 120V | 4000K | 112 |

| Replacement parts | |
|-------------------|---------------------------|
| DFMLWL24 | 2' white acrylic diffuser |
| DFMLWL48 | 4' white acrylic diffuser |



Specifications

INTENDED USE:

Provides an LED lighting platform to deliver general ambient lighting for surface-mount ceiling applications. Light engine delivers long life and excellent color to ensure a quality, low-maintenance light installation. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, and more.

CONSTRUCTION:

The LED wrap is constructed of a metal housing with decorative plastic end caps. The white frosted diffuser provides even illumination and softens the appearance of the LEDs for improved aesthetics.

OPTICS:

2' wrap produces 1,200 lumens and 4' produces 2,900 lumens, both at 50,000 hours life. Thermal formed diffuser is of highly transmissive material to minimize lamp image and provides high-angle brightness control. One piece contemporary design wrap around diffuser softens appearance for improved aesthetics.

ELECTRICAL:

Long-life LEDs, coupled with a high-efficiency driver, provide superior illumination for extended service life. 70% LED lumen maintenance at 60,000 hours (L70/60,000). 0-10V dimming driver, dims to 10%.

LISTINGS:

UL certified to US and Canadian standards. Listed for damp locations. Energy Star® certified.

WARRANTY:

5-year limited warranty.

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions


2'

Length: 24-1/2 (62.2)

Width: 5-1/2 (14.0)

Depth: 2-3/5 (6.6)

Weight: 2.5lbs (1.0kg)



4'

Length: 47-2/5 (120.4)

Width: 5-1/2 (14.0)

Depth: 2-3/5 (6.6)

Weight: 5lbs (1.0kg)

All dimensions are inches (centimeters) unless otherwise indicated.