



RFSF Series

LED Medium Body Strip retrofit with Lens



FEATURES & SPECIFICATIONS

Great Performance Strip Retrofit - now available with Lens. This LED offering is perfect for so many applications.

Designed economically yet with balance and sleek aesthetics. This Kit is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10), or contact factory for more details.

SIZE* (includes strip body)

W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

*All dimensions are inches. Specifications subject to change without notice.

Kit does not include fixture body

2 ft - STANDARD

Example: RFSF24LFRF30W3000LDMV40K

RFSF	24L	FR	F30W3000L	DMV	40K
Series	Length	Lens	Wattage and Lumen	Driver	Kelvin Temperature
RFSF	24L 24"	FR Frosted Lens	F14W1400L 14 System Watts, 1400 Delivered Lumens	DMV 0-10V Dimming 120V - 277V	30K 3000K
Medium Body Strip			F24W2400L 24 System Watts, 2400 Delivered Lumens		35K 3500K
SMRFSF			F30W3000L 30 System Watts, 3000 Delivered Lumens		40K 4000K
Medium Body Strip with Microware Sensor					50K 5000K
					Options
					WP 6 ft. 3 wire 18 gauge whip
					WP10 6 ft. 4 wire 18 gauge whip
					EM 10w Emergency battery backup
					PI1 3 Wire Harness
					PI3 5 Wire Harness

*Consult factory for more options

Catalog Number:
Notes:



RFSF Series

LED Medium Body Strip retrofit with Lens



4 ft - STANDARD

Example: RFSF48LFRF28W2800LDMV40K

Series	Length	Lens	Wattage and Lumen	Driver	Kelvin Temperature
RFSF	48L 48"	FR Frosted Lens	F28W2800L 35 System Watts, 2800 Delivered Lumens	DMV 0-10V Dimming 120V - 277V	30K 3000K
Medium Body Strip			F48W4800L 48 System Watts, 4800 Delivered Lumens		35K 3500K
SMRFSF			F57W5900L 57 System Watts, 5900 Delivered Lumens		40K 4000K
Medium Body Strip with Microware Sensor					50K 5000K
Options					
WP 6 ft. 3 wire 18 gauge whip					
WP10 6 ft. 4 wire 18 gauge whip					
EM 10w Emergency battery backup					
PI1 3 Wire Harness					
PI3 5 Wire Harness					

8 ft - STANDARD

Series	Length	Lens	Wattage and Lumen	Driver	Kelvin Temperature
RFSF	96L 96"	FR Frosted Lens	F57W5900L 57 System Watts, 5900 Delivered Lumens	DMV 0-10V Dimming 120V - 277V	30K 3000K
Medium Body Strip			F62W6200L 62 System Watts, 6200 Delivered Lumens		35K 3500K
SMRFSF			F114W11700L 114 System Watts, 11700 Delivered Lumens		40K 4000K
Medium Body Strip with Microware Sensor					50K 5000K
Options					
WP 6 ft. 3 wire 18 gauge whip					
WP10 6 ft. 4 wire 18 gauge whip					
EM 10w Emergency battery backup					
PI1 3 Wire Harness					
PI3 5 Wire Harness					

*Consult factory for more options

Catalog Number:
Notes: