



# RFSF Series

## LED Medium Body Strip retrofit with Lens



### FEATURES & SPECIFICATIONS

Great Performance Strip Retrofit - now available with Lens. This LED offering is perfect for so many applications.

Designed economically yet with balance and sleek aesthetics. This Kit is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed.

### MOUNTING

Surface mount, chain hung, double stem.

### TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10), or contact factory for more details.

#### SIZE\* (includes strip body)

##### W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

\*All dimensions are inches. Specifications subject to change without notice.

\*\*Kit does not include fixture body\*\*

### 2 ft - STANDARD

Example: RFSF24LFRF30W3000LDMV40K

| RFSF                                    | 24L            | FR                     | F30W3000L   | DMV                                     | 40K                                    |
|---|----------------|------------------------|---|---|--|
| Series                                  | Length         | Lens                   | Wattage and Lumen                                       | Driver                                  | Kelvin Temperature                     |
| <b>RFSF</b>                             | <b>24L</b> 24" | <b>FR</b> Frosted Lens | <b>F14W1400L</b> 14 System Watts, 1400 Delivered Lumens | <b>DMV</b> 0-10V Dimming<br>120V - 277V | <b>30K</b> 3000K                       |
| Medium Body Strip                       |                |                        | <b>F24W2400L</b> 24 System Watts, 2400 Delivered Lumens |   | <b>35K</b> 3500K                       |
| <b>SMRFSF</b>                           |                |                        | <b>F30W3000L</b> 30 System Watts, 3000 Delivered Lumens |   | <b>40K</b> 4000K                       |
| Medium Body Strip with Microware Sensor |                |                        |   |   | <b>50K</b> 5000K                       |
|   |                |                        |   |   | <b>Options</b>                         |
|   |                |                        |   |   | <b>WP</b> 6 ft. 3 wire 18 gauge whip   |
|   |                |                        |   |   | <b>WP10</b> 6 ft. 4 wire 18 gauge whip |
|   |                |                        |   |   | <b>EM</b> 10w Emergency battery backup |
|   |                |                        |   |   | <b>PI1</b> 3 Wire Harness              |
|   |                |                        |   |   | <b>PI3</b> 5 Wire Harness              |

\*Consult factory for more options

|                 |
|-----------------|
| Catalog Number: |
| Notes:          |



# RFSF Series

## LED Medium Body Strip retrofit with Lens



### 4 ft - STANDARD

Example: RFSF48LFRF28W2800LDMV40K

| Series                                  | Length         | Lens                   | Wattage and Lumen                                       | Driver                               | Kelvin Temperature   |
|---|----------------|------------------------|---|--------------------------------------|--|
| <b>RFSF</b>                             | <b>48L</b> 48" | <b>FR</b> Frosted Lens | <b>F28W2800L</b> 35 System Watts, 2800 Delivered Lumens | <b>DMV</b> 0-10V Dimming 120V - 277V | <b>30K</b> 3000K<br><b>35K</b> 3500K<br><b>40K</b> 4000K<br><b>50K</b> 5000K |
| Medium Body Strip                       |                |                        | <b>F48W4800L</b> 48 System Watts, 4800 Delivered Lumens |                                      |  |
| <b>SMRFSF</b>                           |                |                        | <b>F57W5900L</b> 57 System Watts, 5900 Delivered Lumens |                                      |  |
| Medium Body Strip with Microware Sensor |                |                        |   |                                      |  |
|   |                |                        |   |                                      | <b>Options</b>   |
|   |                |                        |   |                                      | <b>WP</b> 6 ft. 3 wire 18 gauge whip   |
|   |                |                        |   |                                      | <b>WP10</b> 6 ft. 4 wire 18 gauge whip                                       |
|   |                |                        |   |                                      | <b>EM</b> 10w Emergency battery backup                                       |
|   |                |                        |   |                                      | <b>PI1</b> 3 Wire Harness  |
|   |                |                        |   |                                      | <b>PI3</b> 5 Wire Harness  |

### 8 ft - STANDARD

| Series                                  | Length         | Lens                   | Wattage and Lumen   | Driver                               | Kelvin Temperature   |
|---|----------------|------------------------|---|--------------------------------------|--|
| <b>RFSF</b>                             | <b>96L</b> 96" | <b>FR</b> Frosted Lens | <b>F57W5900L</b> 57 System Watts, 5900 Delivered Lumens     | <b>DMV</b> 0-10V Dimming 120V - 277V | <b>30K</b> 3000K<br><b>35K</b> 3500K<br><b>40K</b> 4000K<br><b>50K</b> 5000K |
| Medium Body Strip                       |                |                        | <b>F62W6200L</b> 62 System Watts, 6200 Delivered Lumens     |                                      |  |
| <b>SMRFSF</b>                           |                |                        | <b>F114W11700L</b> 114 System Watts, 11700 Delivered Lumens |                                      |  |
| Medium Body Strip with Microware Sensor |                |                        |   |                                      |  |
|   |                |                        |   |                                      | <b>Options</b>   |
|   |                |                        |   |                                      | <b>WP</b> 6 ft. 3 wire 18 gauge whip   |
|   |                |                        |   |                                      | <b>WP10</b> 6 ft. 4 wire 18 gauge whip                                       |
|   |                |                        |   |                                      | <b>EM</b> 10w Emergency battery backup                                       |
|   |                |                        |   |                                      | <b>PI1</b> 3 Wire Harness  |
|   |                |                        |   |                                      | <b>PI3</b> 5 Wire Harness  |

\*Consult factory for more options

|                 |
|-----------------|
| Catalog Number: |
| Notes:          |