

HID LED 35W LOW BAY BYP E26



PRO



35W REPLACES



100-175W
HID

70% Energy Savings

Intentional Uplighting

All High Bay and Low Bay products feature a ring of LEDs mounted around the base to provide visible uplighting for improved aesthetics and comfort



- Ⓞ Direct line voltage 120-277V - Not compatible with ballasts
- Ⓞ Designed for use in low bay applications
- Ⓞ Compatible with E26 sockets
- Ⓞ Visible uplighting for improved aesthetics & comfort
- Ⓞ Exceptional efficacy 126 LPW
- Ⓞ Available in 4000K & 5000K CCT



50,000 H



UNIVERSAL



EFFICACY



WARRANTY



CRI (Ra)



SEMI DIRECTIONAL



SUITABLE FOR ALL LOW BAY APPLICATIONS



HID LED 35W LOW BAY BYP E26

APPLICATIONS

General Lighting



Warehouse



Retail



SPECIFICATIONS

Product Model	98121 35HIDLB/840/BYP/E26	98122 35HIDLB/850/BYP/E26
Type	HID LED	HID LED
Base	E26	E26
Power (W)	35	35
Voltage - Frequency	120-277V	120-277V
Color Temp. (ANSI)	Cool White 4000K	Daylight 5000K
CRI (Ra) (typ.)	82	82
Bare Lamp lumens (lm)	4400	4400
Bare Lamp efficacy (LPW)	126	126
Beam Angle	110°	110°
Dimmable	No	No
Power Factor	0.9	0.9
Rated Lifetime - L70 (hrs.)	50,000	50,000
Temperature Rating	-4°F/-20°C - 113°F/45°C	-4°F/-20°C - 113°F/45°C
Dia. x MOL	6.1"x7.7" (155x196mm)	6.1"x7.7" (155x196mm)
Weight (lb. / g)	1.77lb. / 803g	1.77lb. / 803g

HID EQUIVALENCE

GREEN CREATIVE HID LED		Metal Halide		Mercury Vapor		High Pressure Sodium	
Power	Lumens	Power	Mean Lumens	Power	Mean Lumens	Power	Mean Lumens
35W	4400	100W	5800	175W	6250	70W	5350

* Suitable for damp locations. Not for use where directly exposed to weather or water