# A21 14W DIM. TITANIUM LED SERIES











per lamp\*













- Compact form factor fits all A-lamp applications
- Omnidirectional beam angle
- Exceptional efficacy 114 LPW in Soft White
- Suitable for use in totally enclosed fixtures
- Comfortable warm diffused light













### **A21 PRODUCT FEATURES**

### Suitable for Enclosed Fixtures

This A21 is suitable for use in totally enclosed fixtures and capable of operating in a broad range of applications. Whether it is installed in fully enclosed flushmounts or sconces, this lamp's advanced thermal design ensures optimal performance over the course of its lifetime.









make it an ideal choice for all A-lamp applications including general lighting, downlighting and uplighting.

# A21 14W DIM. TITANIUM LED SERIES









## **SPECIFICATIONS**

| Product                     | 97961                      | 97962                      | 97963                      |
|-----------------------------|----------------------------|----------------------------|----------------------------|
| Model                       | 14A21DIM/827               | 14A21DIM/830               | 14A21DIM/840               |
|                             |                            |                            |                            |
| Туре                        | A21                        | (A21)                      | A21                        |
| Base                        | E26                        | (E26)                      | E26                        |
| Power (W)                   | 14                         | (14)                       | 14                         |
| Voltage - Frequency         | 120V 60Hz                  | 120V 60Hz                  | 120V 60Hz                  |
| Color Temp. (ANSI)          | Soft White 2700K           | Warm White 3000K           | Cool White 4000K           |
| CRI (Ra) (typ.)             | 82                         | 82                         | 82                         |
| Typical lumens (lm)         | 1600                       | (1650)                     | 1700                       |
| Efficacy (LPW)              | 114                        | (118)                      | 121                        |
| Beam Angle                  | 230°                       | (230°)                     | 230°                       |
| Dimmable                    | Yes                        | Yes                        | Yes                        |
| Power Factor                | 0.9                        | 0.9                        | 0.9                        |
| Rated Lifetime - L70 (hrs.) | 25,000                     | (25,000)                   | 25,000                     |
| Temperature Rating          | -4°F / -20°C - 95°F / 35°C | -4°F / -20°C - 95°F / 35°C | -4°F / -20°C - 95°F / 35°C |
| Dia. x MOL                  | 2.64''x5.04'' (67x128mm)   | 2.64"x5.04" (67x128mm)     | 2.64''x5.04'' (67x128mm)   |
| Weight (lb. / g)            | 0.31lb. / 140g             | 0.31lb. / 140g)            | 0.31lb. / 140g             |

<sup>\*</sup> Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$2 incandescent with 1000-hr lifetime, \$24 LED with 25,000-hr lifetime

\*\* Suitable for use in totally enclosed fixtures