A21 14W DIM. TITANIUM LED SERIES



This A21 is suitable for use in totally enclosed fixtures and capable of operating in a broad range of applications. Whether it is installed in fully enclosed flushmounts or sconces, this lamp's advanced thermal design ensures optimal performance over the course of its lifetime.





Smooth & Compact Form Factor



This A21 features a newly designed smooth heatsink for a traditional A-lamp shape. Its sleek design and omnidirectional light output make it an ideal choice for all A-lamp applications including general lighting, downlighting and uplighting.

A21 14W DIM. TITANIUM LED SERIES

APPLICATIONS







SPECIFICATIONS

Product Model	97961 14A21DIM/827	97962 14A21DIM/830	97963 (14A21DIM/849)
Туре	A21	A21	A21
Base	E26	E26	E26
Power (W)	14	14	14
Voltage - Frequency	120V 60Hz	120V 60Hz	(120V 60Hz)
Color Temp. (ANSI)	Soft White 2700K	Warm White 3000K	Cool White 4000K
CRI (Ra) (typ.)	82	82	82
Typical lumens (Im)	1600	1650	(1700)
Efficacy (LPW)	114	118	(121)
Beam Angle	230°	230°	230°
Dimmable	Yes	Yes	Yes
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	25,000	25,000	25,000
Temperature Rating	-4°F / -20°C - 95°F / 35°C	-4°F / -20°C - 95°F / 35°C	<mark>-4°F / -20°C - 95°F / 35°C</mark>)
Dia. x MOL	2.64''x5.04'' (67x128mm)	2.64''x5.04'' (67x128mm)	2.64''x5.04'' (67x128mm)
Weight (lb. / g)	0.31lb. / 140g	0.31lb. / 140g	0.31lb. / 140g

* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$2 incandescent with 1000-hr lifetime, \$24 LED with 25,000-hr lifetime ** Suitable for use in totally enclosed fixtures