



Elite Designer PAR Series

TCP's award winning PARs have just got better. With over 500 options, TCP's new PAR series combines traditional beauty with top-notch technology.

Limitless options for the following applications:

- Track Lights
- Recessed Downlights
- Display Lights
- Outdoor Fixtures that Protect Lamps from the Elements

Great features and benefits:

- Energy Efficient: Up to 85% less energy than halogen replacements.
- Smooth, uniform dimming; also available as non-dimming.
- Long Life: 25,000 hours
- 120W, 90W, 75W, 60W and 50W replacements.
- NEW smooth outer housing.
- Excellent color consistency and high color rendering (CRI).
- Available in 2400K, 2700K, 3000K, 3500K and 4100K.



LED
we know light™



LED 25,000 Hours average rated life, 120 Volts

Applications

Ideal for PAR38, PAR30, and PAR20 flood and spot light applications.


- ✦ Track Lights
- ✦ Recessed Downlights
- ✦ Display Lights
- ✦ Outdoor Fixtures that Protect Lamps from the Elements



Features

Benefits

| | |
|---|---|
| Up to 85% less energy than halogen alternatives | Instant energy savings |
| Long life | Minimizes replacement and maintenance costs |
| Unique full face optic | Provides designer grade light quality with same look as halogen replacement. |
| Smooth, clean outside housing | Seamlessly blends into lighting applications |
| Very low heat generation | Perfect for sensitive display lighting such as art galleries. |
| Excellent Color Consistency and CRI | Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp. |
| Low weight | Track or down light installations are not strained by excess weight. |
| UL approved for damp location | Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors. |
| Shatter resistant | Lower the risk of injury and breakage |



Specifications


| | PAR38 | PAR30LN | PAR30SN | PAR20 |
|------------------------|------------|------------|------------|------------|
| Input Line Voltage: | 120 VAC | 120 VAC | 120 VAC | 120 VAC |
| Input Power | 17 & 14 W | 14 & 12 W | 12 & 10 W | 10 & 8 W |
| Input Line Frequency | 50/60HZ | 50/60HZ | 50/60HZ | 50/60HZ |
| Lamp Life (Rated) | 25,000 hrs | 25,000 hrs | 25,000 hrs | 25,000 hrs |
| Minimum Starting Temp | -30°C | -30°C | -30°C | -30°C |
| Maximum Operating Temp | 40°C | 40°C | 40°C | 40°C |



PAR38



PAR30LN



PAR30SN



PAR20



5 YEAR WARRANTY

For the most up-to-date specs, please visit www.tcpi.com





ELITE Designer Series

LED Dimmable PAR Lamps

Smooth Uniform Dimming

| Item # | Description | Voltage | Wattage | Incandescent Wattage Comparison | Lumens | LPW | CBCP | Beam Angle | CCT | CRI | M.O.L. (inches) | Diameter (inches) | Case Quantity | STK/MTO |
|-----------------|---|---------|---------|---------------------------------------|--------|------|-------|---------------|-------|-----|--------------------|----------------------|------------------|---------|
| PAR38 | | | | | | | | | | | | | | |
| LED17P38D24KFL | Dimmable 17W Smooth PAR38 - 2400K 40° | 120 | 17 | 120 | 1200 | 70.6 | 2024 | 40 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D24KNFL | Dimmable 17W Smooth PAR38 - 2400K 25° | 120 | 17 | 120 | 1200 | 70.6 | 5520 | 25 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D24KSP | Dimmable 17W Smooth PAR38 - 2400K 15° | 120 | 17 | 120 | 1200 | 70.6 | 8832 | 15 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D27KFL | Dimmable 17W Smooth PAR38 - 2700K 40° | 120 | 17 | 120 | 1200 | 70.6 | 2024 | 40 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P38D27KNFL | Dimmable 17W Smooth PAR38 - 2700K 25° | 120 | 17 | 120 | 1200 | 70.6 | 5520 | 25 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P38D27KSP | Dimmable 17W Smooth PAR38 - 2700K 15° | 120 | 17 | 120 | 1200 | 70.6 | 8832 | 15 | 2700K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D30KFL | Dimmable 17W Smooth PAR38 - 3000K 40° | 120 | 17 | 120 | 1250 | 73.5 | 2200 | 40 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P38D30KNFL | Dimmable 17W Smooth PAR38 - 3000K 25° | 120 | 17 | 120 | 1250 | 73.5 | 6000 | 25 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P38D30KSP | Dimmable 17W Smooth PAR38 - 3000K 15° | 120 | 17 | 120 | 1250 | 73.5 | 9600 | 15 | 3000K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D35KFL | Dimmable 17W Smooth PAR38 - 3500K 40° | 120 | 17 | 120 | 1275 | 75.0 | 2266 | 40 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D35KNFL | Dimmable 17W Smooth PAR38 - 3500K 25° | 120 | 17 | 120 | 1275 | 75.0 | 6180 | 25 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D35KSP | Dimmable 17W Smooth PAR38 - 3500K 15° | 120 | 17 | 120 | 1275 | 75.0 | 9888 | 15 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D41KFL | Dimmable 17W Smooth PAR38 - 4100K 40° | 120 | 17 | 120 | 1300 | 76.5 | 2332 | 40 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D41KNFL | Dimmable 17W Smooth PAR38 - 4100K 25° | 120 | 17 | 120 | 1300 | 76.5 | 6360 | 25 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P38D41KSP | Dimmable 17W Smooth PAR38 - 4100K 15° | 120 | 17 | 120 | 1300 | 76.5 | 10176 | 15 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D24KFL | Dimmable 14W Smooth PAR38 - 2400K 40° | 120 | 14 | 90 | 1050 | 75.0 | 1840 | 40 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D24KNFL | Dimmable 14W Smooth PAR38 - 2400K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D24KSP | Dimmable 14W Smooth PAR38 - 2400K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D27KFL | Dimmable 13.5W Smooth PAR38 - 2700K 40° | 120 | 13.5 | 90 | 1050 | 75.0 | 1840 | 40 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P38D27KNFL | Dimmable 14W Smooth PAR38 - 2700K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P38D27KSP | Dimmable 14W Smooth PAR38 - 2700K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2700K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D30KFL | Dimmable 14W Smooth PAR38 - 3000K 40° | 120 | 14 | 90 | 1100 | 78.6 | 2000 | 40 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P38D30KNFL | Dimmable 14W Smooth PAR38 - 3000K 25° | 120 | 14 | 90 | 1100 | 78.6 | 5300 | 25 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P38D30KSP | Dimmable 14W Smooth PAR38 - 3000K 15° | 120 | 14 | 90 | 1100 | 78.6 | 8480 | 15 | 3000K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D35KFL | Dimmable 14W Smooth PAR38 - 3500K 40° | 120 | 14 | 90 | 1125 | 80.4 | 2060 | 40 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D35KNFL | Dimmable 14W Smooth PAR38 - 3500K 25° | 120 | 14 | 90 | 1125 | 80.4 | 5459 | 25 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D35KSP | Dimmable 14W Smooth PAR38 - 3500K 15° | 120 | 14 | 90 | 1125 | 80.4 | 8734 | 15 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D41KFL | Dimmable 14W Smooth PAR38 - 4100K 40° | 120 | 14 | 90 | 1150 | 82.1 | 2120 | 40 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D41KNFL | Dimmable 14W Smooth PAR38 - 4100K 25° | 120 | 14 | 90 | 1150 | 82.1 | 5618 | 25 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P38D41KSP | Dimmable 14W Smooth PAR38 - 4100K 15° | 120 | 14 | 90 | 1150 | 82.1 | 8989 | 15 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| PAR30 | | | | | | | | | | | | | | |
| LED14P30D24KFL | Dimmable 14W Smooth PAR30 - 2400K 40° | 120 | 14 | 90 | 1050 | 75.0 | 1840 | 40 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D24KNFL | Dimmable 14W Smooth PAR30 - 2400K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D24KSP | Dimmable 14W Smooth PAR30 - 2400K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D27KFL | Dimmable 14W Smooth PAR30 - 2700K 40° | 120 | 14 | 90 | 1050 | 75.0 | 1840 | 40 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P30D27KNFL | Dimmable 14W Smooth PAR30 - 2700K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P30D27KSP | Dimmable 14W Smooth PAR30 - 2700K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2700K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D30KFL | Dimmable 14W Smooth PAR30 - 3000K 40° | 120 | 14 | 90 | 1100 | 78.6 | 2000 | 40 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P30D30KNFL | Dimmable 13.5W Smooth PAR30 - 3000K 25° | 120 | 13.5 | 90 | 1050 | 78.6 | 5300 | 25 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P30D30KSP | Dimmable 14W Smooth PAR30 - 3000K 15° | 120 | 14 | 90 | 1100 | 78.6 | 8480 | 15 | 3000K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D35KFL | Dimmable 14W Smooth PAR30 - 3500K 40° | 120 | 14 | 90 | 1125 | 80.4 | 2060 | 40 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D35KNFL | Dimmable 14W Smooth PAR30 - 3500K 25° | 120 | 14 | 90 | 1125 | 80.4 | 5459 | 25 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D35KSP | Dimmable 14W Smooth PAR30 - 3500K 15° | 120 | 14 | 90 | 1125 | 80.4 | 8734 | 15 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D41KFL | Dimmable 14W Smooth PAR30 - 4100K 40° | 120 | 14 | 90 | 1150 | 82.1 | 2120 | 40 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D41KNFL | Dimmable 14W Smooth PAR30 - 4100K 25° | 120 | 14 | 90 | 1150 | 82.1 | 5618 | 25 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P30D41KSP | Dimmable 14W Smooth PAR30 - 4100K 15° | 120 | 14 | 90 | 1150 | 82.1 | 8989 | 15 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D24KFL | Dimmable 12W Smooth PAR30 - 2400K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D24KNFL | Dimmable 12W Smooth PAR30 - 2400K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D24KSP | Dimmable 12W Smooth PAR30 - 2400K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D27KFL | Dimmable 12W Smooth PAR30 - 2700K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P30D27KNFL | Dimmable 12W Smooth PAR30 - 2700K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P30D27KSP | Dimmable 12W Smooth PAR30 - 2700K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2700K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D30KFL | Dimmable 12W Smooth PAR30 - 3000K 40° | 120 | 12 | 75 | 825 | 68.8 | 1400 | 40 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P30D30KNFL | Dimmable 12W Smooth PAR30 - 3000K 25° | 120 | 12 | 75 | 825 | 68.8 | 3750 | 25 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P30D30KSP | Dimmable 12W Smooth PAR30 - 3000K 15° | 120 | 12 | 75 | 825 | 68.8 | 6000 | 15 | 3000K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D35KFL | Dimmable 12W Smooth PAR30 - 3500K 40° | 120 | 12 | 75 | 850 | 70.8 | 1442 | 40 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D35KNFL | Dimmable 12W Smooth PAR30 - 3500K 25° | 120 | 12 | 75 | 850 | 70.8 | 3863 | 25 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D35KSP | Dimmable 12W Smooth PAR30 - 3500K 15° | 120 | 12 | 75 | 850 | 70.8 | 6180 | 15 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D41KFL | Dimmable 12W Smooth PAR30 - 4100K 40° | 120 | 12 | 75 | 875 | 72.9 | 1484 | 40 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D41KNFL | Dimmable 12W Smooth PAR30 - 4100K 25° | 120 | 12 | 75 | 875 | 72.9 | 3975 | 25 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P30D41KSP | Dimmable 12W Smooth PAR30 - 4100K 15° | 120 | 12 | 75 | 875 | 72.9 | 6360 | 15 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |





ELITE Designer Series

LED Dimmable PAR Lamps

Smooth Uniform Dimming

| Item # | Description | Voltage | Wattage | Incandescent Wattage Comparison | Lumens | LPW | CBC | Beam Angle | CCT | CRI | M.O.L. (inches) | Diameter (inches) | Case Quantity | STK/MTO |
|------------------|--|---------|---------|---------------------------------|--------|------|------|------------|-------|-----|-----------------|-------------------|---------------|---------|
| PAR30SN | | | | | | | | | | | | | | |
| LED12P30SD24KFL | Dimmable 12W Smooth PAR30 Short Neck - 2400K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD24KNFL | Dimmable 12W Smooth PAR30 Short Neck - 2400K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD24KSP | Dimmable 12W Smooth PAR30 Short Neck - 2400K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD27KFL | Dimmable 12W Smooth PAR30 Short Neck - 2700K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30SD27KNFL | Dimmable 12W Smooth PAR30 Short Neck - 2700K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30SD27KSP | Dimmable 12W Smooth PAR30 Short Neck - 2700K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2700K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD30KFL | Dimmable 12W Smooth PAR30 Short Neck - 3000K 40° | 120 | 12 | 75 | 825 | 68.8 | 1400 | 40 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30SD30KNFL | Dimmable 12W Smooth PAR30 Short Neck - 3000K 25° | 120 | 12 | 75 | 825 | 68.8 | 3750 | 25 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30SD30KSP | Dimmable 12W Smooth PAR30 Short Neck - 3000K 15° | 120 | 12 | 75 | 825 | 68.8 | 6000 | 15 | 3000K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD35KFL | Dimmable 12W Smooth PAR30 Short Neck - 3500K 40° | 120 | 12 | 75 | 850 | 70.8 | 1442 | 40 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD35KNFL | Dimmable 12W Smooth PAR30 Short Neck - 3500K 25° | 120 | 12 | 75 | 850 | 70.8 | 3863 | 25 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD35KSP | Dimmable 12W Smooth PAR30 Short Neck - 3500K 15° | 120 | 12 | 75 | 850 | 70.8 | 6180 | 15 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD41KFL | Dimmable 12W Smooth PAR30 Short Neck - 4100K 40° | 120 | 12 | 75 | 875 | 72.9 | 1484 | 40 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD41KNFL | Dimmable 12W Smooth PAR30 Short Neck - 4100K 25° | 120 | 12 | 75 | 875 | 72.9 | 3975 | 25 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30SD41KSP | Dimmable 12W Smooth PAR30 Short Neck - 4100K 15° | 120 | 12 | 75 | 875 | 72.9 | 6360 | 15 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD24KFL | Dimmable 10W Smooth PAR30 Short Neck - 2400K 40° | 120 | 10 | 60 | 600 | 60.0 | 985 | 40 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD24KNFL | Dimmable 10W Smooth PAR30 Short Neck - 2400K 25° | 120 | 10 | 60 | 600 | 60.0 | 2639 | 25 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD24KSP | Dimmable 10W Smooth PAR30 Short Neck - 2400K 15° | 120 | 10 | 60 | 600 | 60.0 | 4221 | 15 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD27KFL | Dimmable 10W Smooth PAR30 Short Neck - 2700K 40° | 120 | 10 | 60 | 600 | 60.0 | 985 | 40 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30SD27KNFL | Dimmable 10W Smooth PAR30 Short Neck - 2700K 25° | 120 | 10 | 60 | 600 | 60.0 | 2639 | 25 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30SD27KSP | Dimmable 10W Smooth PAR30 Short Neck - 2700K 15° | 120 | 10 | 60 | 600 | 60.0 | 4221 | 15 | 2700K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD30KFL | Dimmable 10W Smooth PAR30 Short Neck - 3000K 40° | 120 | 10 | 60 | 650 | 65.0 | 1071 | 40 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30SD30KNFL | Dimmable 10W Smooth PAR30 Short Neck - 3000K 25° | 120 | 10 | 60 | 650 | 65.0 | 2868 | 25 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30SD30KSP | Dimmable 10W Smooth PAR30 Short Neck - 3000K 15° | 120 | 10 | 60 | 650 | 65.0 | 4588 | 15 | 3000K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD35KFL | Dimmable 10W Smooth PAR30 Short Neck - 3500K 40° | 120 | 10 | 60 | 675 | 67.5 | 1103 | 40 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD35KNFL | Dimmable 10W Smooth PAR30 Short Neck - 3500K 25° | 120 | 10 | 60 | 675 | 67.5 | 2954 | 25 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD35KSP | Dimmable 10W Smooth PAR30 Short Neck - 3500K 15° | 120 | 10 | 60 | 675 | 67.5 | 4726 | 15 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD41KFL | Dimmable 10W Smooth PAR30 Short Neck - 4100K 40° | 120 | 10 | 60 | 700 | 70.0 | 1135 | 40 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD41KNFL | Dimmable 10W Smooth PAR30 Short Neck - 4100K 25° | 120 | 10 | 60 | 700 | 70.0 | 3040 | 25 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30SD41KSP | Dimmable 10W Smooth PAR30 Short Neck - 4100K 15° | 120 | 10 | 60 | 700 | 70.0 | 4863 | 15 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| PAR20 | | | | | | | | | | | | | | |
| LED10P20D24KFL | Dimmable 10W Smooth PAR20 - 2400K 40° | 120 | 10 | 60 | 600 | 60.0 | TBD | 40 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P20D24KNFL | Dimmable 10W Smooth PAR20 - 2400K 25° | 120 | 10 | 60 | 600 | 60.0 | TBD | 25 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P20D27KFL | Dimmable 10W Smooth PAR20 - 2700K 40° | 120 | 10 | 60 | 600 | 60.0 | TBD | 40 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P20D27KNFL | Dimmable 10W Smooth PAR20 - 2700K 25° | 120 | 10 | 60 | 600 | 60.0 | TBD | 25 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P20D30KFL | Dimmable 10W Smooth PAR20 - 3000K 40° | 120 | 10 | 60 | 650 | 65.0 | TBD | 40 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P20D30KNFL | Dimmable 10W Smooth PAR20 - 3000K 25° | 120 | 10 | 60 | 650 | 65.0 | TBD | 25 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P20D35KFL | Dimmable 10W Smooth PAR20 - 3500K 40° | 120 | 10 | 60 | 675 | 67.5 | TBD | 40 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P20D35KNFL | Dimmable 10W Smooth PAR20 - 3500K 25° | 120 | 10 | 60 | 675 | 67.5 | TBD | 25 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P20D41KFL | Dimmable 10W Smooth PAR20 - 4100K 40° | 120 | 10 | 60 | 700 | 70.0 | TBD | 40 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P20D41KNFL | Dimmable 10W Smooth PAR20 - 4100K 25° | 120 | 10 | 60 | 700 | 70.0 | TBD | 25 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P20D24KFL | Dimmable 8W Smooth PAR20 - 2400K 40° | 120 | 8 | 50 | 500 | 62.5 | 754 | 40 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P20D24KNFL | Dimmable 8W Smooth PAR20 - 2400K 25° | 120 | 8 | 50 | 500 | 62.5 | 2070 | 25 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P20D27KFL | Dimmable 8W Smooth PAR20 - 2700K 40° | 120 | 8 | 50 | 500 | 62.5 | 754 | 40 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P20D27KNFL | Dimmable 8W Smooth PAR20 - 2700K 25° | 120 | 8 | 50 | 500 | 62.5 | 2070 | 25 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P20D30KFL | Dimmable 8W Smooth PAR20 - 3000K 40° | 120 | 8 | 50 | 515 | 64.4 | 820 | 40 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P20D30KNFL | Dimmable 8W Smooth PAR20 - 3000K 25° | 120 | 8 | 50 | 515 | 64.4 | 2250 | 25 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P20D35KFL | Dimmable 8W Smooth PAR20 - 3500K 40° | 120 | 8 | 50 | 525 | 65.6 | 845 | 40 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P20D35KNFL | Dimmable 8W Smooth PAR20 - 3500K 25° | 120 | 8 | 50 | 525 | 65.6 | 2318 | 25 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P20D41KFL | Dimmable 8W Smooth PAR20 - 4100K 40° | 120 | 8 | 50 | 530 | 66.3 | 869 | 40 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P20D41KNFL | Dimmable 8W Smooth PAR20 - 4100K 25° | 120 | 8 | 50 | 530 | 66.3 | 2385 | 25 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |



5 YEAR WARRANTY

For the most up-to-date specs, please visit www.tcp.com

TCP, Inc.
325 Campus Dr. | Aurora, Ohio 44202 | P: 1-800-324-1496 | tcp.com

©TCP, Inc. MAY 2013/50595c





ELITE Designer Series

LED Non-Dimmable PAR Lamps

| Item # | Description | Voltage | Wattage | Incandescent Wattage Comparison | Lumens | LPW | CBC | Beam Angle | CCT | CRI | M.O.L. (inches) | Diameter (inches) | Case Quantity | STK/MTO |
|----------------|---|---------|---------|---------------------------------------|--------|------|-------|---------------|-------|-----|--------------------|----------------------|------------------|---------|
| PAR38 | | | | | | | | | | | | | | |
| LED17P3824KFL | Non-Dimmable 17W Smooth PAR38 - 2400K 40° | 120 | 17 | 120 | 1200 | 70.6 | 2024 | 40 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3824KNFL | Non-Dimmable 17W Smooth PAR38 - 2400K 25° | 120 | 17 | 120 | 1200 | 70.6 | 5520 | 25 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3824KSP | Non-Dimmable 17W Smooth PAR38 - 2400K 15° | 120 | 17 | 120 | 1200 | 70.6 | 8832 | 15 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3827KFL | Non-Dimmable 17W Smooth PAR38 - 2700K 40° | 120 | 17 | 120 | 1200 | 70.6 | 2024 | 40 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P3827KNFL | Non-Dimmable 17W Smooth PAR38 - 2700K 25° | 120 | 17 | 120 | 1200 | 70.6 | 5520 | 25 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P3827KSP | Non-Dimmable 17W Smooth PAR38 - 2700K 15° | 120 | 17 | 120 | 1200 | 70.6 | 8832 | 15 | 2700K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3830KFL | Non-Dimmable 17W Smooth PAR38 - 3000K 40° | 120 | 17 | 120 | 1250 | 73.5 | 2200 | 40 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P3830KNFL | Non-Dimmable 17W Smooth PAR38 - 3000K 25° | 120 | 17 | 120 | 1250 | 73.5 | 6000 | 25 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED17P3830KSP | Non-Dimmable 17W Smooth PAR38 - 3000K 15° | 120 | 17 | 120 | 1250 | 73.5 | 9600 | 15 | 3000K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3835KFL | Non-Dimmable 17W Smooth PAR38 - 3500K 40° | 120 | 17 | 120 | 1275 | 75.0 | 2266 | 40 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3835KNFL | Non-Dimmable 17W Smooth PAR38 - 3500K 25° | 120 | 17 | 120 | 1275 | 75.0 | 6180 | 25 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3835KSP | Non-Dimmable 17W Smooth PAR38 - 3500K 15° | 120 | 17 | 120 | 1275 | 75.0 | 9888 | 15 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3841KFL | Non-Dimmable 17W Smooth PAR38 - 4100K 40° | 120 | 17 | 120 | 1300 | 76.5 | 2332 | 40 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3841KNFL | Non-Dimmable 17W Smooth PAR38 - 4100K 25° | 120 | 17 | 120 | 1300 | 76.5 | 6360 | 25 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED17P3841KSP | Non-Dimmable 17W Smooth PAR38 - 4100K 15° | 120 | 17 | 120 | 1300 | 76.5 | 10176 | 15 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3824KFL | Non-Dimmable 14W Smooth PAR38 - 2400K 40° | 120 | 14 | 90 | 1050 | 75.0 | 1840 | 40 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3824KNFL | Non-Dimmable 14W Smooth PAR38 - 2400K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3824KSP | Non-Dimmable 14W Smooth PAR38 - 2400K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2400K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3827KFL | Non-Dimmable 14W Smooth PAR38 - 2700K 40° | 120 | 14 | 90 | 1050 | 75.0 | 1840 | 40 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P3827KNFL | Non-Dimmable 14W Smooth PAR38 - 2700K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2700K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P3827KSP | Non-Dimmable 14W Smooth PAR38 - 2700K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2700K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3830KFL | Non-Dimmable 14W Smooth PAR38 - 3000K 40° | 120 | 14 | 90 | 1100 | 78.6 | 2000 | 40 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P3830KNFL | Non-Dimmable 14W Smooth PAR38 - 3000K 25° | 120 | 14 | 90 | 1100 | 78.6 | 5300 | 25 | 3000K | 82 | 5.3 | 4.8 | 12 | STK |
| LED14P3830KSP | Non-Dimmable 14W Smooth PAR38 - 3000K 15° | 120 | 14 | 90 | 1100 | 78.6 | 8480 | 15 | 3000K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3835KFL | Non-Dimmable 14W Smooth PAR38 - 3500K 40° | 120 | 14 | 90 | 1125 | 80.4 | 2060 | 40 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3835KNFL | Non-Dimmable 14W Smooth PAR38 - 3500K 25° | 120 | 14 | 90 | 1125 | 80.4 | 5459 | 25 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3835KSP | Non-Dimmable 14W Smooth PAR38 - 3500K 15° | 120 | 14 | 90 | 1125 | 80.4 | 8734 | 15 | 3500K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3841KFL | Non-Dimmable 14W Smooth PAR38 - 4100K 40° | 120 | 14 | 90 | 1150 | 82.1 | 2120 | 40 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3841KNFL | Non-Dimmable 14W Smooth PAR38 - 4100K 25° | 120 | 14 | 90 | 1150 | 82.1 | 5618 | 25 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| LED14P3841KSP | Non-Dimmable 14W Smooth PAR38 - 4100K 15° | 120 | 14 | 90 | 1150 | 82.1 | 8989 | 15 | 4100K | 82 | 5.3 | 4.8 | 12 | MTO |
| PAR30 | | | | | | | | | | | | | | |
| LED14P3024KFL | Non-Dimmable 14W Smooth PAR30 - 2400K 40° | 120 | 14 | 90 | 1050 | 75.0 | 1840 | 40 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3024KNFL | Non-Dimmable 14W Smooth PAR30 - 2400K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3024KSP | Non-Dimmable 14W Smooth PAR30 - 2400K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3027KFL | Non-Dimmable 14W Smooth PAR30 - 2700K 40° | 120 | 14 | 90 | 1050 | 75.0 | 1840 | 40 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P3027KNFL | Non-Dimmable 14W Smooth PAR30 - 2700K 25° | 120 | 14 | 90 | 1050 | 75.0 | 4876 | 25 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P3027KSP | Non-Dimmable 14W Smooth PAR30 - 2700K 15° | 120 | 14 | 90 | 1050 | 75.0 | 7802 | 15 | 2700K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3030KFL | Non-Dimmable 14W Smooth PAR30 - 3000K 40° | 120 | 14 | 90 | 1100 | 78.6 | 2000 | 40 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P3030KNFL | Non-Dimmable 14W Smooth PAR30 - 3000K 25° | 120 | 14 | 90 | 1100 | 78.6 | 5300 | 25 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED14P3030KSP | Non-Dimmable 14W Smooth PAR30 - 3000K 15° | 120 | 14 | 90 | 1100 | 78.6 | 8480 | 15 | 3000K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3035KFL | Non-Dimmable 14W Smooth PAR30 - 3500K 40° | 120 | 14 | 90 | 1125 | 80.4 | 2060 | 40 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3035KNFL | Non-Dimmable 14W Smooth PAR30 - 3500K 25° | 120 | 14 | 90 | 1125 | 80.4 | 5459 | 25 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3035KSP | Non-Dimmable 14W Smooth PAR30 - 3500K 15° | 120 | 14 | 90 | 1125 | 80.4 | 8734 | 15 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3041KFL | Non-Dimmable 14W Smooth PAR30 - 4100K 40° | 120 | 14 | 90 | 1150 | 82.1 | 2120 | 40 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3041KNFL | Non-Dimmable 14W Smooth PAR30 - 4100K 25° | 120 | 14 | 90 | 1150 | 82.1 | 5618 | 25 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED14P3041KSP | Non-Dimmable 14W Smooth PAR30 - 4100K 15° | 120 | 14 | 90 | 1150 | 82.1 | 8989 | 15 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3024KFL | Non-Dimmable 12W Smooth PAR30 - 2400K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3024KNFL | Non-Dimmable 12W Smooth PAR30 - 2400K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3024KSP | Non-Dimmable 12W Smooth PAR30 - 2400K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2400K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3027KFL | Non-Dimmable 12W Smooth PAR30 - 2700K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P3027KNFL | Non-Dimmable 12W Smooth PAR30 - 2700K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2700K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P3027KSP | Non-Dimmable 12W Smooth PAR30 - 2700K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2700K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3030KFL | Non-Dimmable 12W Smooth PAR30 - 3000K 40° | 120 | 12 | 75 | 825 | 68.8 | 1400 | 40 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P3030KNFL | Non-Dimmable 12W Smooth PAR30 - 3000K 25° | 120 | 12 | 75 | 825 | 68.8 | 3750 | 25 | 3000K | 82 | 4.8 | 3.8 | 12 | STK |
| LED12P3030KSP | Non-Dimmable 12W Smooth PAR30 - 3000K 15° | 120 | 12 | 75 | 825 | 68.8 | 6000 | 15 | 3000K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3035KFL | Non-Dimmable 12W Smooth PAR30 - 3500K 40° | 120 | 12 | 75 | 850 | 70.8 | 1442 | 40 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3035KNFL | Non-Dimmable 12W Smooth PAR30 - 3500K 25° | 120 | 12 | 75 | 850 | 70.8 | 3863 | 25 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3035KSP | Non-Dimmable 12W Smooth PAR30 - 3500K 15° | 120 | 12 | 75 | 850 | 70.8 | 6180 | 15 | 3500K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3041KFL | Non-Dimmable 12W Smooth PAR30 - 4100K 40° | 120 | 12 | 75 | 875 | 72.9 | 1484 | 40 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3041KNFL | Non-Dimmable 12W Smooth PAR30 - 4100K 25° | 120 | 12 | 75 | 875 | 72.9 | 3975 | 25 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |
| LED12P3041KSP | Non-Dimmable 12W Smooth PAR30 - 4100K 15° | 120 | 12 | 75 | 875 | 72.9 | 6360 | 15 | 4100K | 82 | 4.8 | 3.8 | 12 | MTO |



ELITE Designer Series

LED Non-Dimmable PAR Lamps

| Item # | Description | Voltage | Wattage | Incandescent Wattage Comparison | Lumens | LPW | CBCP | Beam Angle | CCT | CRI | M.O.L. (inches) | Diameter (inches) | Case Quantity | STK/MTO |
|-----------------|--|---------|---------|---------------------------------------|--------|------|------|---------------|-------|-----|--------------------|----------------------|------------------|---------|
| PAR30SN | | | | | | | | | | | | | | |
| LED12P30S24KFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 2400K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S24KNFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 2400K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S24KSP | Non-Dimmable 12W Smooth PAR30 Short Neck - 2400K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S27KFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 2700K 40° | 120 | 12 | 75 | 800 | 66.7 | 1288 | 40 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30S27KNFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 2700K 25° | 120 | 12 | 75 | 800 | 66.7 | 3450 | 25 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30S27KSP | Non-Dimmable 12W Smooth PAR30 Short Neck - 2700K 15° | 120 | 12 | 75 | 800 | 66.7 | 5520 | 15 | 2700K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S30KFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 3000K 40° | 120 | 12 | 75 | 825 | 68.8 | 1400 | 40 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30S30KNFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 3000K 25° | 120 | 12 | 75 | 825 | 68.8 | 3750 | 25 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED12P30S30KSP | Non-Dimmable 12W Smooth PAR30 Short Neck - 3000K 15° | 120 | 12 | 75 | 825 | 68.8 | 6000 | 15 | 3000K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S35KFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 3500K 40° | 120 | 12 | 75 | 850 | 70.8 | 1442 | 40 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S35KNFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 3500K 25° | 120 | 12 | 75 | 850 | 70.8 | 3863 | 25 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S35KSP | Non-Dimmable 12W Smooth PAR30 Short Neck - 3500K 15° | 120 | 12 | 75 | 850 | 70.8 | 6180 | 15 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S41KFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 4100K 40° | 120 | 12 | 75 | 875 | 72.9 | 1484 | 40 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S41KNFL | Non-Dimmable 12W Smooth PAR30 Short Neck - 4100K 25° | 120 | 12 | 75 | 875 | 72.9 | 3975 | 25 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED12P30S41KSP | Non-Dimmable 12W Smooth PAR30 Short Neck - 4100K 15° | 120 | 12 | 75 | 875 | 72.9 | 6360 | 15 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S24KFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 2400K 40° | 120 | 10 | 60 | 600 | 60.0 | 985 | 40 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S24KNFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 2400K 25° | 120 | 10 | 60 | 600 | 60.0 | 2639 | 25 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S24KSP | Non-Dimmable 10W Smooth PAR30 Short Neck - 2400K 15° | 120 | 10 | 60 | 600 | 60.0 | 4221 | 15 | 2400K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S27KFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 2700K 40° | 120 | 10 | 60 | 600 | 60.0 | 985 | 40 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30S27KNFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 2700K 25° | 120 | 10 | 60 | 600 | 60.0 | 2639 | 25 | 2700K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30S27KSP | Non-Dimmable 10W Smooth PAR30 Short Neck - 2700K 15° | 120 | 10 | 60 | 600 | 60.0 | 4221 | 15 | 2700K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S30KFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 3000K 40° | 120 | 10 | 60 | 650 | 65.0 | 1071 | 40 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30S30KNFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 3000K 25° | 120 | 10 | 60 | 650 | 65.0 | 2868 | 25 | 3000K | 82 | 3.5 | 3.8 | 12 | STK |
| LED10P30S30KSP | Non-Dimmable 10W Smooth PAR30 Short Neck - 3000K 15° | 120 | 10 | 60 | 650 | 65.0 | 4588 | 15 | 3000K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S35KFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 3500K 40° | 120 | 10 | 60 | 675 | 67.5 | 1103 | 40 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S35KNFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 3500K 25° | 120 | 10 | 60 | 675 | 67.5 | 2954 | 25 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S35KSP | Non-Dimmable 10W Smooth PAR30 Short Neck - 3500K 15° | 120 | 10 | 60 | 675 | 67.5 | 4726 | 15 | 3500K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S41KFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 4100K 40° | 120 | 10 | 60 | 700 | 70.0 | 1135 | 40 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S41KNFL | Non-Dimmable 10W Smooth PAR30 Short Neck - 4100K 25° | 120 | 10 | 60 | 700 | 70.0 | 3040 | 25 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| LED10P30S41KSP | Non-Dimmable 10W Smooth PAR30 Short Neck - 4100K 15° | 120 | 10 | 60 | 700 | 70.0 | 4863 | 15 | 4100K | 82 | 3.5 | 3.8 | 12 | MTO |
| PAR20 | | | | | | | | | | | | | | |
| LED10P2024KFL | Non-Dimmable 10W Smooth PAR20 - 2400K 40° | 120 | 10 | 60 | 600 | 60.0 | TBD | 40 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P2024KNFL | Non-Dimmable 10W Smooth PAR20 - 2400K 25° | 120 | 10 | 60 | 600 | 60.0 | TBD | 25 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P2027KFL | Non-Dimmable 10W Smooth PAR20 - 2700K 40° | 120 | 10 | 60 | 600 | 60.0 | TBD | 40 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P2027KNFL | Non-Dimmable 10W Smooth PAR20 - 2700K 25° | 120 | 10 | 60 | 600 | 60.0 | TBD | 25 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P2030KFL | Non-Dimmable 10W Smooth PAR20 - 3000K 40° | 120 | 10 | 60 | 650 | 65.0 | TBD | 40 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P2030KNFL | Non-Dimmable 10W Smooth PAR20 - 3000K 25° | 120 | 10 | 60 | 650 | 65.0 | TBD | 25 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED10P2035KFL | Non-Dimmable 10W Smooth PAR20 - 3500K 40° | 120 | 10 | 60 | 675 | 67.5 | TBD | 40 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P2035KNFL | Non-Dimmable 10W Smooth PAR20 - 3500K 25° | 120 | 10 | 60 | 675 | 67.5 | TBD | 25 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P2041KFL | Non-Dimmable 10W Smooth PAR20 - 4100K 40° | 120 | 10 | 60 | 700 | 70.0 | TBD | 40 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED10P2041KNFL | Non-Dimmable 10W Smooth PAR20 - 4100K 25° | 120 | 10 | 60 | 700 | 70.0 | TBD | 25 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P2024KFL | Non-Dimmable 8W Smooth PAR20 - 2400K 40° | 120 | 8 | 50 | 500 | 62.5 | 754 | 40 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P2024KNFL | Non-Dimmable 8W Smooth PAR20 - 2400K 25° | 120 | 8 | 50 | 500 | 62.5 | 2070 | 25 | 2400K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P2027KFL | Non-Dimmable 8W Smooth PAR20 - 2700K 40° | 120 | 8 | 50 | 500 | 62.5 | 754 | 40 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P2027KNFL | Non-Dimmable 8W Smooth PAR20 - 2700K 25° | 120 | 8 | 50 | 500 | 62.5 | 2070 | 25 | 2700K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P2030KFL | Non-Dimmable 8W Smooth PAR20 - 3000K 40° | 120 | 8 | 50 | 515 | 64.4 | 820 | 40 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P2030KNFL | Non-Dimmable 8W Smooth PAR20 - 3000K 25° | 120 | 8 | 50 | 515 | 64.4 | 2250 | 25 | 3000K | 82 | 3.5 | 2.5 | 12 | STK |
| LED8P2035KFL | Non-Dimmable 8W Smooth PAR20 - 3500K 40° | 120 | 8 | 50 | 525 | 65.6 | 845 | 40 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P2035KNFL | Non-Dimmable 8W Smooth PAR20 - 3500K 25° | 120 | 8 | 50 | 525 | 65.6 | 2318 | 25 | 3500K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P2041KFL | Non-Dimmable 8W Smooth PAR20 - 4100K 40° | 120 | 8 | 50 | 530 | 66.3 | 869 | 40 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |
| LED8P2041KNFL | Non-Dimmable 8W Smooth PAR20 - 4100K 25° | 120 | 8 | 50 | 530 | 66.3 | 2385 | 25 | 4100K | 82 | 3.5 | 2.5 | 12 | MTO |



5 YEAR WARRANTY

For the most up-to-date specs, please visit www.tcpinc.com

