



LED T8 SERIES


Double-Ended Bypass

COMMERCIAL SPEC GRADE

Replaces 32W 4ft Fluorescent T8



Superior All-Around Light Distribution



Coated Shatter-Resistant Glass



Proprietary IC-Driver design allows for high efficiency and exceptional longterm performance



ARCHIPELAGO® Light Engine produces uniform light output from end-to-end



FEATURES

- No More Need to Re-Wire the Fixture: Direct-Wire Installation
- Double-Ended Bypass: Keep Your Existing Sockets for L/N
- Full Glass Lens with 310° Light Distribution
- Uniform Light Output From End-to-End
- UL + NSF/ANSI Standard 2 + DLC4 QPL Listed
- Instant-ON with No Flicker
- 5-Year Warranty


Specifications and Technical Data (T8 | Double-Ended Bypass)

MODEL	BASE TYPE	WATTS / EQV.	LUMEN	CCT	LENGTH	VOLTAGE	CRI	THD	CARTON QTY	LIGHT DISTRIBUTION
LBW8F1240	G13	12W / 32W	1750LM	4100K	4 FT	120-277V	83	<20%	16	310°
LBW8F1240	G13	12W / 32W	1800LM	5000K	4 FT	120-277V	83	<20%	16	310°

* Suitable for use in totally enclosed fixtures.

** Suitable for damp locations. Not for use where exposed to the weather or moisture.

Installation Configuration



Double-Ended Bypass

Light Distribution Curve

