



S9913

14T8/LED/48-830/BP 120-277V
 14 watt T8 LED; Medium bi-pin base; 3000K; 50000 average
 rated hours; 1700 lumens

Features

- All glass tube
- Direct wire 120-277V line voltage*
- NSF/ANSI Standard 2 Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9913

*Existing wiring to both sockets can remain in place
 *Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base
S9913	045923099137	120-277	14	25W-32W	T8	Medium Bi-Pin	G13

Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
14T8/LED/48-830/BP 120-277V	Non-Dimmable	White	48"	1.00"	1700	50000	3000

Color	CRI	Beam Spread Deg	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed
Halogen White	82	220	10	Box	PA4VXQZF	Yes	Yes

UL Classification	Warranty
cULus - Damp Location Rated	5 Year Limited