



# LED T8 SERIES

## BYPass LED T8 - 4FT

### COMMERCIAL SPEC GRADE

Replaces 32W 4ft Fluorescent T8




Superior All-Around Light Distribution



Coated Shatter-Resistant Glass



Proprietary IC-Driver design allows for high efficiency and exceptional longterm performance



Light Engine produces uniform light output from end-to-end.



### FEATURES

- BYPass the Ballast - Easy Retrofit Installation
- Full Glass Lens with 310° Light Distribution
- Uniform Light Output From End-to-End
- Universal Input Voltage - 120-277V
- UL + NSF/ANSI Standard 2 + DLC4.0 QPL Listed
- Instant-ON with No Flicker

### Specifications and Technical Data

MODEL	BASE TYPE	WATTS / EQV.	LUMEN	CCT	LENGTH	VOLTAGE	CRI	THD	CARTON QTY	LIGHT DISTRIBUTION
LBP8F1730B	Bi-Pin G13	12.5W / 32W	1650LM	3000K	4 FT	120-277V	83	<20%	16	310°
LBP8F1735B	Bi-Pin G13	12.5W / 32W	1650LM	3500K	4 FT	120-277V	83	<20%	16	310°
LBP8F1741B	Bi-Pin G13	12.5W / 32W	1750LM	4100K	4 FT	120-277V	83	<20%	16	310°
LBP8F1745B	Bi-Pin G13	12.5W / 32W	1750LM	4500K	4 FT	120-277V	83	<20%	16	310°
LBP8F1750B	Bi-Pin G13	12.5W / 32W	1800LM	5000K	4 FT	120-277V	83	<20%	16	310°
LBP8F1930B	Bi-Pin G13	13.5W / 32W	1800LM	3000K	4 FT	120-277V	83	<20%	16	310°
LBP8F1935B	Bi-Pin G13	13.5W / 32W	1800LM	3500K	4 FT	120-277V	83	<20%	16	310°
LBP8F1941B	Bi-Pin G13	13.5W / 32W	1900LM	4100K	4 FT	120-277V	83	<20%	16	310°
LBP8F1945B	Bi-Pin G13	13.5W / 32W	1900LM	4500K	4 FT	120-277V	83	<20%	16	310°
LBP8F1950B	Bi-Pin G13	13.5W / 32W	2000LM	5000K	4 FT	120-277V	83	<20%	16	310°
LBP8F2130B	Bi-Pin G13	15.0W / 32W	1900LM	3000K	4 FT	120-277V	83	<20%	16	310°
LBP8F2135B	Bi-Pin G13	15.0W / 32W	1900LM	3500K	4 FT	120-277V	83	<20%	16	310°
LBP8F2141B	Bi-Pin G13	15.0W / 32W	2000LM	4100K	4 FT	120-277V	83	<20%	16	310°
LBP8F2145B	Bi-Pin G13	15.0W / 32W	2000LM	4500K	4 FT	120-277V	83	<20%	16	310°
LBP8F2150B	Bi-Pin G13	15.0W / 32W	2100LM	5000K	4 FT	120-277V	83	<20%	16	310°
LBP8F2530B	Bi-Pin G13	18.5W / 32W	2400LM	3000K	4 FT	120-277V	83	<20%	16	310°
LBP8F2535B	Bi-Pin G13	18.5W / 32W	2400LM	3500K	4 FT	120-277V	83	<20%	16	310°
LBP8F2541B	Bi-Pin G13	18.5W / 32W	2500LM	4100K	4 FT	120-277V	83	<20%	16	310°
LBP8F2545B	Bi-Pin G13	18.5W / 32W	2500LM	4500K	4 FT	120-277V	83	<20%	16	310°
LBP8F2550B	Bi-Pin G13	18.5W / 32W	2600LM	5000K	4 FT	120-277V	83	<20%	16	310°

\* Suitable for use in totally enclosed fixtures

\*\* Suitable for damp locations. Not for use where exposed to the weather or moisture

