



LED T8 SERIES


BYPass LED T8 - 4FT

COMMERCIAL SPEC GRADE

Replaces 32W 4ft Fluorescent T8



Superior All-Around Light Distribution



Coated Shatter-Resistant Glass



Proprietary IC-Driver design allows for high efficiency and exceptional longterm performance



ARCHIPELAGO® Light Engine produces uniform light output from end-to-end



FEATURES

- BYPass the Ballast - Easy Retrofit Installation
- Full Glass Lens with 310° Light Distribution
- Uniform Light Output From End-to-End
- Universal Input Voltage - 120-277V
- UL + NSF/ANSI Standard 2 + DLC4.0 QPL Listed
- Instant-ON with No Flicker

Specifications and Technical Data

| MODEL | BASE TYPE | WATTS / EQV. | LUMEN | CCT | LENGTH | VOLTAGE | CRI | THD | CARTON QTY | LIGHT DISTRIBUTION |
|------------|------------|--------------|--------|-------|--------|----------|-----|------|------------|--------------------|
| LBP8F1730B | Bi-Pin G13 | 12.5W / 32W | 1650LM | 3000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1735B | Bi-Pin G13 | 12.5W / 32W | 1650LM | 3500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1741B | Bi-Pin G13 | 12.5W / 32W | 1750LM | 4100K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1745B | Bi-Pin G13 | 12.5W / 32W | 1750LM | 4500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1750B | Bi-Pin G13 | 12.5W / 32W | 1800LM | 5000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1930B | Bi-Pin G13 | 13.5W / 32W | 1800LM | 3000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1935B | Bi-Pin G13 | 13.5W / 32W | 1800LM | 3500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1941B | Bi-Pin G13 | 13.5W / 32W | 1900LM | 4100K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1945B | Bi-Pin G13 | 13.5W / 32W | 1900LM | 4500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F1950B | Bi-Pin G13 | 13.5W / 32W | 2000LM | 5000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2130B | Bi-Pin G13 | 15.0W / 32W | 1900LM | 3000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2135B | Bi-Pin G13 | 15.0W / 32W | 1900LM | 3500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2141B | Bi-Pin G13 | 15.0W / 32W | 2000LM | 4100K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2145B | Bi-Pin G13 | 15.0W / 32W | 2000LM | 4500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2150B | Bi-Pin G13 | 15.0W / 32W | 2100LM | 5000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2530B | Bi-Pin G13 | 18.5W / 32W | 2400LM | 3000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2535B | Bi-Pin G13 | 18.5W / 32W | 2400LM | 3500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2541B | Bi-Pin G13 | 18.5W / 32W | 2500LM | 4100K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2545B | Bi-Pin G13 | 18.5W / 32W | 2500LM | 4500K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |
| LBP8F2550B | Bi-Pin G13 | 18.5W / 32W | 2600LM | 5000K | 4 FT | 120-277V | 83 | <20% | 16 | 310° |

* Suitable for use in totally enclosed fixtures

** Suitable for damp locations. Not for use where exposed to the weather or moisture



LM-80
LM-79

