



# LED T5 SERIES

## BYPass LED T5 - 4FT

### COMMERCIAL SPEC GRADE

Replaces 54W 4ft Fluorescent T5



#### FEATURES

- BYPass, 120-277V for 54W Fluorescent T5 Replacement
- Full Glass Lens with 310° Light Distribution
- Uniform Light Output From End-to-End
- UL + NSF/ANSI Standard 2 + DLC4.0 QPL Listed
- Instant-ON with No Flicker
- 5-Year Warranty

#### Superior All-Around Light Distribution



#### Coated Shatter-Resistant Glass



Designed for high efficiency and versatility, the IC-Driver allows for exceptional BYPass performance



Seamless output from end-to-end, ARCHIPELAGO® Light Engine allows for fully uniform light output



#### Specifications and Technical Data (T5 | BYPass)

MODEL	BASE TYPE	WATTS / EQV.	LUMEN	CCT	LENGTH	VOLTAGE	CRI	THD	CARTON QTY	LIGHT DISTRIBUTION
LBP5F3335A	Bi-Pin G5	25.5W / 54W	3300LM	3500K	4 FT	120-277V	83	<20%	16	310°
LBP5F3341A	Bi-Pin G5	25.5W / 54W	3300LM	4100K	4 FT	120-277V	83	<20%	16	310°
LBP5F3345A	Bi-Pin G5	25.5W / 54W	3300LM	4500K	4 FT	277V	83	<20%	16	310°
LBP5F3350A	Bi-Pin G5	25.5W / 54W	3300LM	5000K	4 FT	120-277V	83	<20%	16	310°

\* Suitable for use in totally enclosed fixtures

\*\* Suitable for damp locations. Not for use where exposed to the weather or moisture

#### Light Distribution Curve

