



S9914

14T8/LED/48-835/BP 120-277V
 14 watt T8 LED; Medium bi-pin base; 3500K; 50000 average
 rated hours; 1700 lumens

Features

- All glass tube
- Direct wire 120-277V line voltage*
- Double ended wiring
- NSF/ANSI Standard 2 Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9914

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S9914	045923099144	120-277	14	50/60Hz	25W-32W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	14T8/LED/48-835/BP 120-277V	Non-Dimmable	White	48"	1.00"	1700	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	Package Type	CEC Status	DLC ID:
3500	Neutral White	82	220	10	Box	Lawful for sale in California	PZ8RBRB2 DLC Search
RoHS Compliant	UL or ETL Listed	UL Classification	Warranty				
Yes	Yes	cULus - Damp Location Rated	5 Year Limited				



The SATCO logo, featuring a stylized white icon of a person's head and shoulders to the left of the word "SATCO" in a bold, white, sans-serif font, followed by a registered trademark symbol (®).