



# S29395

80W/LED/HID/5000K/100-277V/EX39  
80 watt - LED HID Replacement; 5000K; Mogul extended base;  
100-277 volts

### Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- Built-in surge protection - 5KV
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

### Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in surge protection

Shatter resistant materials, acceptable for use in food prep areas



S29395

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	Incandescent Equivalent	Fluorescent Equivalent
-------------	--------------	-----	---------------	-------	---------------------	-------------------------	------------------------

S29395	Hi-Pro	045923293955	100 - 277	80	50/60Hz	400W	100W	
HID Equivalent	Base	ANSI Base	Lamp Code		Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches
320W	Mogul Extended	EX39	80W/LED/HID/5000K/100-277V/EX39		Non-Dimmable	White	9-1/4"	5.87"
Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		Pack
10640	50000	5000	Daylight White	80+	300	-20C (-4F) to a maximum of +65C (+149F)		12
Package Type	CEC Status	DLC ID:	RoHS Compliant	UL Classification		Thermal Management		
Box	Lawful for sale in California	<a href="#">PLU7PE5MD5JQ</a>	Yes	cULus - Wet Location Rated				