

S28717

120W/LED/HID/5000K/277-347V/EX39 120 watt - LED HID Replacement; 5000K; Mogul extended base; 277-347 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 277 347V
 UL approved for totally enclosed fixtures
 Damp location IP65 rated

- For outdoor & indoor use
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C
- · Safety chain included

Additional Technical Specifications

- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
 Power Factor >0.9

Minimum Compartment Size							
Length Width Depth							
17.3 inch 9.25 inch 9.25 inch							



S28717

Item Number	Product Line	UPC	Voltage	Watts	Incandesce Equivalen		Fluorescent Equivalent		HID Equivale	
S28717	Hi-Pro	045923287176	277-347	120	750W		200W		200W 600W	
Base	ANSI	Lamp Cod	e	Dir	mmable/Non-	Finish	MOL In	MOD		Initial

Base	ANSI Base	Lamp Code	Dimmable/Non- Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Mogul Extended	EX39	120W/LED/HID/5000K/277- 347V/EX39	Non-Dimmable	White	10-3/8"	5-7/8"	16000

Average Rated Hours	Kelvin Temp	Color	CRI Beam S De	()nerating Lemperature	Pack	Package Type
------------------------	----------------	-------	------------------	------------------------	------	--------------

50000	5000	Daylight White	80+	300		-20C (-4F) to a maximum of +65C (+149F)		Вох
CEC Status	DLC ID:			RoHS Compliant	UL Classification			
Lawful for sale in California	PL0GLD9J32WB; PL2RICVYUIE8			Yes	cULus - Wet Location Rated			