

22180 - F282D/835/4P

GE 2D® T6 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse









CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-In Bulb T6

Base GR10q-4
Equivalent Wattage (NOM) 100.0 W
Rated Life (NOM) 10000.0 h
Starting Temperature (MIN) -4.0 °C
Mercury Content (NOM) 3.0 mg
Picograms of Mercury (NOM) 174.4186 pg
Primary Application Facilities;Retail

Display; Hospitality; Office; Restaurant; W.

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 2050.0
Mean Lumens (NOM) 1720.0
Nominal Initial Lumens per Watt (NOM)
Color Temperature (NOM) 3500.0 K
Color Rendering Index (CRI) 82.0
(NOM)

ELECTRICAL CHARACTERISTICS

 Wattage (NOM)
 28.0

 Voltage (NOM)
 120.0

 Current (max) (NOM)
 5.25 A

 Open Circuit Voltage Across
 198.0 V

 Starter (MIN)

Preheat Voltage (MIN) 4.25 V
Current Crest Factor (MAX) 1.7
Supply Current Frequency 20.0 Hz
(NOM)

DIMENSIONS

Maximum Overall Length 8.110 in(206.0 mm)

(MOL) (NOM)

Nominal Length (NOM) 8.100 in(205.7 mm) Base Face to Top of Lamp 1.250 in(31.8 mm)

(NOM)

PRODUCT INFORMATION

Product Code 22180
Description F282D/835/4P

Standard Package Case

Standard Package GTIN 00043168221801

Standard Package Quantity 20
Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 20

Package

UPC 043168981859

NOTES

- 10-watt, 16-watt and 28-watt 2D lamps may be operated in any position. 21-watt, 38-watt, 39-watt, and 55-watt 2D lamps must be used with the leg market (a) in the diagram below the bend (b), in order to avoid overheating the end of the cap marked (c).
- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life