



# S29861

9WPLV/LED/850/DR/4P  
 9W LED PL 4-Pin; 5000K; 1000 Lumens; G24q base; 50000  
 Average rated hours; 120 Deg. beam spread

### Features

- Replaces 26, 32, and 42 watt CFLs
- Direct Replacement - for use with Electronic, Instant Start, Rapid Start, and Programmed Start ballasts with no rewiring required. Ballast required.
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving
- Long life - 50,000 hours
- 5 year warranty



S29861

| Item Number             | UPC                                     | Watts         | Fluorescent Equivalent        | Lamp Shape          | Base           | Lamp Code           | Dimmable/Non-Dimmable                  |
|-------------------------|---|---------------|-------------------------------|---------------------|----------------|---------------------|--|
| S29861                  | 045923298615                            | 9             | 26, 32, and 42 watt CFL       | PL                  | G24q           | 9WPLV/LED/850/DR/4P | Non-Dimmable                           |
| Finish                  | MOL In Inches                           | MOD In Inches | Initial Lumens                | Average Rated Hours | Kelvin Temp    | Color               | CRI                                    |
| Frost                   | 4-11/16"                                | 1-15/16"      | 1000                          | 50000               | 5000           | Daylight White      | 82                                     |
| Beam Spread Deg         | Operating Temperature                   | Package Type  | CEC Status                    | DLC ID:             | RoHS Compliant | UL or ETL Listed    | UL Classification                      |
| 120                     | -20C (-4F) to a maximum of +45C (+113F) | Box           | Lawful for sale in California | PL0EEYBT3BN0        | Yes            | Yes                 | cULus Classified - Damp Location Rated |
| 5 Year Limited Warranty |   |               |                               |                     |                |                     |  |