

[E-CATALOG\(/CATALOG/\)](#) > [SPECIALTY\(/CATALOG/C/SPECIALTY\)](#) > [RETAIL, OFFICE & FACILITIES\(/CATALOG/C/SPECIALTY_RETAIL_OFFICE_N_FACILITIES\)](#) > [RESTAURANT\(/CATALOG/C/SPECIALTY_RETAIL_OFFICE_N_FACILITIES_RESTAURANT\)](#) > [GE ECOLUX® BIAx® T4 - FACILITIES. RETAIL DISPLAY. HOSPITALITY. OFFICE. RESTAURANT. WAREHOUSE\(/CATALOG/P/97595\)](#)

e-Catalog Search



0



F13DBX/830/ECO4P

97595

69
lumens/watt

GE Ecolux® Biax® T4 - Facilities. Retail Display. Hospitality. Office. Restaurant. Warehouse

[Specifications](#)

[Additional Content](#)

GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	0 °C
Mercury-Picogram per mean lm hr	198.7
Primary Application	Standard Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Lamp Count	1
Base	G24q-1
Bulb Shape	T4

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	60 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	13 W

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	755 lm
Nominal Initial Lumen per Watt	69
Color Rendering Index-CRI	82

DIMENSIONS

Base Face to Top of Lamp	4.4 in
--------------------------	--------

Nominal Length	5.0 in
Bulb Max Overall Length-MOL	4.9 in
PACKAGING INFORMATION	
Alternative Unit Of Measure	PACK
Standard Package Quantity	5
Ean UPC	043168975957
Standard Package GTIN	30043168975958
Length	7.35 in
Width	3.15 in
Height	5.85 in
Volume	0.07838 cuft
Gross Weight	0.78 lb
Pack Level Description	Pack
Sales Unit	Inner Pack
UCC	043168975957