



AP SERIES POWERSPORTS BATTERIES

HIGH PERFORMANCE CONVENTIONAL

UPG No. 42005

APH16A-A(AB)

Equivalent to HYB16A-AB

Specification


Nominal Voltage	12 Volts
Nominal Capacity (10H-R)	16 Ah
Approximate Weight (With Acid)	11.0 lbs. (5.0 kgs)
Recommended Maximum Charging Current	1.6 A
Maximum Charging Voltage	14.8 V @ 25°C
Terminal Type	G
Warranty	1 Year Full Replacement

Physical Dimensions: in (mm)

L: 6.28 (160) **W:** 3.51 (89.0) **H:** 6.97 (177)



Due to continuous improvements to our products, product may vary slightly from depiction.



Front



Side



Terminals

Filling Instructions

- Before filling, ensure your new battery is the correct size for your vehicle. Once the battery is filled, it cannot be returned to vendor.
- Only use the acid pack that comes with your battery.
- Fill all cells to the "FULL" mark and wait 30 minutes.
- After 30 minutes, any cell that has settled below the "FULL" mark should be topped off to the "FULL" mark.
- Replace the sealer caps before charging the battery.

Charging Instructions

- Charge the battery fully before installing.
- Never charge this battery with a charger that delivers more than 1.6 amps of current. Larger chargers will harm the battery.
- Kinetik recommends our 12V 500mA charger (D1730).