

**LED-8057M 75W Post Top Retrofit**



**Models**

LED-8057MXX-A, 120-277VAC, cULus, 3000K, 4000K & 5000K CCT  
 LED-8057MXXC-A, 347VAC, cUL, 3000K, 4000K or 5000K CCT

**Description**

Light Efficient Design's Post Top/Bollard retrofits replace HID lamps up to 400W HID. Advanced Active Cooling technology improves thermal performance and delivers the highest light output along with longer LED and driver life versus lamps limited to passive cooling. All models are tested by UL under 1598C that insures that retrofitted fixture retains safety certification as well as approved by UL for enclosed fixtures.

**Features**

- 75W LED Replaces 320W MH or HPS HID Lamps
- Up to 10,500 lumen output and 140 LPW efficacy
- Available in EX39 Mogul screw base
- UL approved for damp environments and enclosed fixtures
- Advanced active cooling: Active cooling and dynamic temperature control
- Integrated 6kA surge
- 50,000 hour rated LED life (supported by LM80 and ISTMT reports (see website))
- 5 Year Limited Warranty - see website for details
- Insect/dust resistant housing



Mogul Base Models Only  
(See details below)



**TECHNICAL SPECIFICATIONS - USA 120-277V - ALL MODELS cULus**

MODEL	VOLTAGE	WATTAGE	LUMENS*	LPW*	REPLACES	BASE	CCT	CRI*	THD*	PF*	R9*	Duv*	LIGHT DISTRIBUTION	DIMMABLE
LED-8057M30-A	120-277V	75W	9750	130	UP TO 320W HID	EX39 Mogul	3000K	>80	<20%	>.90	0	0	Directional / 120°	No
LED-8057M40-A			10500	140			4000K	>80	<20%	>.90	0	0		
LED-8057M50-A			10500	140			5000K	>80	<20%	>.90	0	0		

**TECHNICAL SPECIFICATIONS - CANADA 347V - ALL MODELS cUL**

MODEL	VOLTAGE	WATTAGE	LUMENS*	LPW*	REPLACES	BASE	CCT	CRI*	THD*	PF*	R9*	Duv*	LIGHT DISTRIBUTION	DIMMABLE
LED-8057M30C-A	347V	75W	9750	130	UP TO 320W HID	EX39 Mogul	3000K	>80	<20%	>.90	0	0	Directional / 120°	No
LED-8057M40C-A			10500	140			4000K	>80	<20%	>.90	0	0		
LED-8057M50C-A			10500	140			5000K	>80	<20%	>.90	0	0		

**PACKAGING SPECIFICATIONS**

MODEL	PRODUCT DIMENSION	PRODUCT WEIGHT	UNIT CARTON DIMENSION	UNIT CTN WT	SHIPPER CARTON DIMENSION	SHIPPER CTN WT	CARTON QUANTITY
LED-8057M	7.3 X 5.7 in.	0	0	0	0	0	4

**UPC / UCC**

**DESIGN LIGHTS CONSORTIUM QPL CERTIFICATION SUMMARY (E39 MODELS ONLY)**

MODEL	PRODUCT UPC	CARTON UCC	QPL CATEGORY 1	PRODUCT CODE	FAMILY CODE	QPL CATEGORY 2	PRODUCT CODE	FAMILY CODE
LED-8057M30-A	8440060 8316 8	10 8440060 8316 5	N/A	N/A	N/A	0	0	0
LED-8057M40-A	8440060 8289 5	10 8440060 8289 2	N/A	N/A	N/A	0	0	0
LED-8057M50-A	8440060 8290 1	10 8440060 8290 8	N/A	N/A	N/A	0	0	0
LED-8057M30C-A	8440060 8317 5	10 8440060 8317 2	N/A	N/A	N/A	0	0	0
LED-8057M40C-A	8440060 8293 2	10 8440060 8293 9	N/A	N/A	N/A	0	0	0
LED-8057M50C-A	8440060 8294 9	10 8440060 8294 6	N/A	N/A	N/A	0	0	0

**ENERGY SAVING vs. HID**

**ZONAL LUMENS/ LUX DISTANCE DATA (see LM79 for more information)**

**Mounting Orientation**

<b>LED Lamp Power (watts)</b>	75	<table border="1"> <thead> <tr> <th colspan="3">Zonal Lumen Summary</th> <th colspan="6">Lumens Per Zone</th> </tr> <tr> <th>Zone</th> <th>Lumens</th> <th>% Luminaire</th> <th>Zone</th> <th>Lumens</th> <th>% Total</th> <th>Zone</th> <th>Lumens</th> <th>% Total</th> </tr> </thead> <tbody> <tr> <td>0-30</td> <td>726.4</td> <td>6.9%</td> <td>0-10</td> <td>61.2</td> <td>0.6%</td> <td>90-100</td> <td>418.4</td> <td>4%</td> </tr> <tr> <td>0-40</td> <td>1,589.7</td> <td>15.1%</td> <td>10-20</td> <td>207.5</td> <td>2.0%</td> <td>100-110</td> <td>240.4</td> <td>2.3%</td> </tr> <tr> <td>0-60</td> <td>4,786.8</td> <td>45.3%</td> <td>20-30</td> <td>457.7</td> <td>4.3%</td> <td>110-120</td> <td>169.8</td> <td>1.6%</td> </tr> <tr> <td>60-90</td> <td>4,697.7</td> <td>44.5%</td> <td>30-40</td> <td>863.3</td> <td>8.2%</td> <td>120-130</td> <td>104.5</td> <td>1%</td> </tr> <tr> <td>70-100</td> <td>3,199.0</td> <td>30.3%</td> <td>40-50</td> <td>1,380.3</td> <td>13.1%</td> <td>130-140</td> <td>74.7</td> <td>0.7%</td> </tr> <tr> <td>90-120</td> <td>828.5</td> <td>7.8%</td> <td>50-60</td> <td>1,816.8</td> <td>17.2%</td> <td>140-150</td> <td>43.7</td> <td>0.4%</td> </tr> <tr> <td>0-90</td> <td>9,484.5</td> <td>89.8%</td> <td>60-70</td> <td>1,917.1</td> <td>18.2%</td> <td>150-160</td> <td>18.5</td> <td>0.2%</td> </tr> <tr> <td>90-180</td> <td>1,076.6</td> <td>10.2%</td> <td>70-80</td> <td>1,661.5</td> <td>15.7%</td> <td>160-170</td> <td>5.5</td> <td>0.1%</td> </tr> <tr> <td>0-180</td> <td>10,561.1</td> <td>100%</td> <td>80-90</td> <td>1,119.1</td> <td>10.6%</td> <td>170-180</td> <td>1.2</td> <td>0%</td> </tr> </tbody> </table>						Zonal Lumen Summary			Lumens Per Zone						Zone	Lumens	% Luminaire	Zone	Lumens	% Total	Zone	Lumens	% Total	0-30	726.4	6.9%	0-10	61.2	0.6%	90-100	418.4	4%	0-40	1,589.7	15.1%	10-20	207.5	2.0%	100-110	240.4	2.3%	0-60	4,786.8	45.3%	20-30	457.7	4.3%	110-120	169.8	1.6%	60-90	4,697.7	44.5%	30-40	863.3	8.2%	120-130	104.5	1%	70-100	3,199.0	30.3%	40-50	1,380.3	13.1%	130-140	74.7	0.7%	90-120	828.5	7.8%	50-60	1,816.8	17.2%	140-150	43.7	0.4%	0-90	9,484.5	89.8%	60-70	1,917.1	18.2%	150-160	18.5	0.2%	90-180	1,076.6	10.2%	70-80	1,661.5	15.7%	160-170	5.5	0.1%	0-180	10,561.1	100%	80-90	1,119.1	10.6%	170-180	1.2	0%	<table border="1"> <thead> <tr> <th>BASE DOWN</th> <th>BASE UP</th> <th>HORIZONTAL</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td>APPROVED</td> <td>APPROVED</td> <td>APPROVED</td> </tr> </tbody> </table>			BASE DOWN	BASE UP	HORIZONTAL				APPROVED	APPROVED	APPROVED
Zonal Lumen Summary								Lumens Per Zone																																																																																																														
Zone	Lumens	% Luminaire	Zone	Lumens	% Total	Zone	Lumens	% Total																																																																																																														
0-30	726.4	6.9%	0-10	61.2	0.6%	90-100	418.4	4%																																																																																																														
0-40	1,589.7	15.1%	10-20	207.5	2.0%	100-110	240.4	2.3%																																																																																																														
0-60	4,786.8	45.3%	20-30	457.7	4.3%	110-120	169.8	1.6%																																																																																																														
60-90	4,697.7	44.5%	30-40	863.3	8.2%	120-130	104.5	1%																																																																																																														
70-100	3,199.0	30.3%	40-50	1,380.3	13.1%	130-140	74.7	0.7%																																																																																																														
90-120	828.5	7.8%	50-60	1,816.8	17.2%	140-150	43.7	0.4%																																																																																																														
0-90	9,484.5	89.8%	60-70	1,917.1	18.2%	150-160	18.5	0.2%																																																																																																														
90-180	1,076.6	10.2%	70-80	1,661.5	15.7%	160-170	5.5	0.1%																																																																																																														
0-180	10,561.1	100%	80-90	1,119.1	10.6%	170-180	1.2	0%																																																																																																														
BASE DOWN	BASE UP	HORIZONTAL																																																																																																																				
APPROVED	APPROVED	APPROVED																																																																																																																				
<b>HID Lamp Power (watts)</b>	320							<table border="1"> <thead> <tr> <th colspan="3">THERMAL SPECIFICATIONS</th> </tr> </thead> <tbody> <tr> <td>Minimum Fixture Size</td> <td>OPERATING TEMPERATURE</td> <td>-40°F to +122°F</td> </tr> </tbody> </table>			THERMAL SPECIFICATIONS			Minimum Fixture Size	OPERATING TEMPERATURE	-40°F to +122°F																																																																																																						
THERMAL SPECIFICATIONS																																																																																																																						
Minimum Fixture Size	OPERATING TEMPERATURE	-40°F to +122°F																																																																																																																				
<b>HID Ballast Power (watts)</b>	48							<table border="1"> <thead> <tr> <th colspan="3">IN-SITU TEMP MEASUREMENT/L70</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>7.5</td> <td>LED TEMPERATURE*</td> <td>68</td> </tr> <tr> <td>Height</td> <td>8.5</td> <td>L70 LED LUMEN MAINTAINENCE*</td> <td>&gt;60,000</td> </tr> <tr> <td>Volume (Cu. In.)</td> <td>478.125</td> <td colspan="2">* FROM ISTMT REPORT AT 77°F</td> </tr> </tbody> </table>			IN-SITU TEMP MEASUREMENT/L70			Width	7.5	LED TEMPERATURE*	68	Height	8.5	L70 LED LUMEN MAINTAINENCE*	>60,000	Volume (Cu. In.)	478.125	* FROM ISTMT REPORT AT 77°F																																																																																														
IN-SITU TEMP MEASUREMENT/L70																																																																																																																						
Width	7.5	LED TEMPERATURE*	68																																																																																																																			
Height	8.5	L70 LED LUMEN MAINTAINENCE*	>60,000																																																																																																																			
Volume (Cu. In.)	478.125	* FROM ISTMT REPORT AT 77°F																																																																																																																				
<b>Total power Savings (watts)</b>	293																																																																																																																					
<b>Annual Energy Savings</b>	\$ 165																																																																																																																					
<b>Lifetime Energy Savings over 50,000 hrs)</b>	\$ 1,612																																																																																																																					