

# PLT &



Item#: **81657**  
**A19 TOUGH COAT LAMP**  
INCANDESCENT

## FEATURES

- Silicone coated to provide resistance to shattering and weather proofing
- Rough service filament to endure the challenge of harsh conditions
- Provides a soft diffused light with less than 3% loss of lumens

## APPLICATION

Used in household, commercial spaces, track lighting and recessed downlights.

## ELECTRICAL

|         |      |
|---------|------|
| Wattage | 75W  |
| Voltage | 130V |

## LIGHTING PERFORMANCE

|                           |                 |
|---------------------------|-----------------|
| Lumens                    | 700             |
| Lumens Per Watt (Lm/W)    | 9               |
| Color Temperature (CCT)   | 2700K           |
| Dimmable Lighting Control | <i>Dimmable</i> |

## LIFESPAN

|                      |        |
|----------------------|--------|
| Average Life (Hours) | 10,000 |
|----------------------|--------|

## CONSTRUCTION

|                     |                         |
|---------------------|-------------------------|
| Housing             | Glass / Silicone Coated |
| Base / Power Supply | E26 - Medium            |
| Lens                | Clear                   |

## QUALIFICATIONS


*Published lumens on products are approximate and may vary slightly.*

Item#: **81657**  
**A19 TOUGH COAT LAMP**

**DIMENSIONS** (Inches)

|                      |      |
|----------------------|------|
| Length (MOL)         | 4.2" |
| Width/Diameter (MOD) | 2.4" |
| Weight (Lbs)         | 0.1  |

Line drawings may not be to scale and are for general reference only.



| PACKAGING         |              | UPC          | DIMENSIONS (LxWxH)  | GROSS WEIGHT (Lbs) |
|-------------------|--------------|--------------|---------------------|--------------------|
| Master Carton     | 120          | --           | 19.1" x 10" x 12.8" | 11.4               |
| Individual Box    | 1            | 811768023947 | --                  | --                 |
| Country of Origin | China        |              |                     |                    |
| HS Tariff         | 8539.22.8060 |              |                     |                    |

**ORDERING**

| ITEM# | DESCRIPTION                          | CASE |
|-------|--------------------------------------|------|
| 81657 | 75A19/RS/TOUGH COAT - SUPERIOR LIFE® | 120  |

**ADDITIONAL INFORMATION:**

- When the temperature is within 392°F, the silicone coating life time will reach 2000 hrs and the silicone coating will still perform well.
- If the temperature exceeds 392°F, the silicone life time will quickly drop off.