

LED 4 ft. Double-Ended T8 Tube

PLT[®]



FEATURES

- Compatible with both shunted and non-shunted sockets
- Meets DLC performance and efficiency criteria
- Equivalent to a 32-Watt fluorescent T8 tube
- 4000 Kelvin cool white color temperature
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- DLC® Part Number: PLTSP33214
- Bi-Pin G13 base

APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	Life Hours	Warranty
PLTSP33214	4000	2200	82	17	120-277	YES	Bi-Pin	50,000	5 Year

SPECIFICATIONS

DIMMABLE	NO LUMENS	2,200
DLC LISTED	YES VOLTAGE	120-277
SAFETY RATING	UL DAMP LENS	FROSTED GLASS
CRI	82 BASE TYPE	G13
COLOR	COOL WHITE BALLAST TYPE	BALLAST BYPASS
COLOR TEMPERATURE	4000K DIAMETER	0.98 IN.
LIFE HOURS	50,000 LENGTH	47.67 IN.
WATTAGE	17 WATTS FLUORESCENT EQUAL.....	32 WATT