

LED 2 ft. Double-Ended T8 Tube

PLT[®]



FEATURES

- Compatible with both shunted and non-shunted sockets
- Meets DLC performance and efficiency criteria
- 3500 Kelvin color matched for halogen bulbs
- Equivalent to a 17-Watt fluorescent T8 tube
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- DLC® Part Number: PLTSP41213
- Bi-Pin G13 base

APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	LED L70 Life Hours	Warranty
LEDT-10076	3500	1100	82	9	120-277	YES	Bi-Pin	≥100,000	5 Year

SPECIFICATIONS

DIMMABLE	NO LUMENS	1,100
DLC LISTED	YES VOLTAGE	120-277
SAFETY RATING	UL DAMP LENS	FROSTED GLASS
CRI	82 BASE TYPE	G13
COLOR	HALOGEN WHITE BALLAST TYPE	BALLAST BYPASS
COLOR TEMPERATURE	3500K DIAMETER	0.98 IN.
LED L70 LIFE HOURS	≥100,000 LENGTH	23.67 IN.
WATTAGE	9 WATTS FLUORESCENT EQUAL	17 WATT