

LED

2 ft. Double-Ended T8 Tube



FEATURES

- Compatible with both shunted and non-shunted sockets
- Meets DLC performance and efficiency criteria
- 3500 Kelvin color matched for halogen bulbs
- Equivalent to a 17-Watt fluorescent T8 tube
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- DLC® Part Number: PLTSP41213
- Bi-Pin G13 base

APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	Life Hours	Warranty
------	--------	--------	-----	---------	---------	------	------	------------	----------

LEDT-10076	3500	1100	82	9	120-277	YES	Bi-Pin	50,000	5 Year
------------	------	------	----	---	---------	-----	--------	--------	--------

SPECIFICATIONS

DIMMABLE	NO	LUMENS	1,100
DLC LISTED	YES	VOLTAGE	120-277
SAFETY RATING	UL DAMP	LENS	FROSTED GLASS
CRI	82	BASE TYPE	G13
COLOR	HALOGEN WHITE	BALLAST TYPE	BALLAST BYPASS
COLOR TEMPERATURE	3500K	DIAMETER	0.98 IN.
LIFE HOURS	50,000	LENGTH	23.67 IN.
WATTAGE	9 WATTS	FLUORESCENT EQUAL	17 WATT