

# LED

## 2 ft. Double-Ended T8 Tube



### FEATURES

- Compatible with both shunted and non-shunted sockets
- Meets DLC performance and efficiency criteria
- Equivalent to a 17-Watt fluorescent T8 tube
- Frosted glass lens evenly diffuses light
- 5000 Kelvin daylight color temperature
- UL listed for use in damp locations
- DLC® Part Number: PLTSP41215
- Bi-Pin G13 base

### APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	LED L70 Life Hours	Warranty
LEDT-10078	5000	1150	82	9	120-277	YES	Bi-Pin	≥100,000	5 Year

### SPECIFICATIONS

DIMMABLE .....	NO	LUMENS .....	1,150
DLC LISTED .....	YES	VOLTAGE .....	120-277
SAFETY RATING .....	UL DAMP	LENS .....	FROSTED GLASS
CRI .....	82	BASE TYPE .....	G13
COLOR .....	DAYLIGHT WHITE	BALLAST TYPE .....	BALLAST BYPASS
COLOR TEMPERATURE .....	5000K	DIAMETER .....	0.98 IN.
LED L70 LIFE HOURS .....	≥100,000	LENGTH .....	23.67 IN.
WATTAGE .....	9 WATTS	FLUORESCENT EQUAL.....	17 WATT