

LED

4 ft. Direct Wire T5 Tube



FEATURES

- Meets DLC performance and efficiency criteria
- Equivalent to a 54-Watt fluorescent tube
- Frosted glass lens to evenly diffuse light
- 5000 Kelvin daylight color temperature
- UL listed for use in damp locations
- DLC® Part Number: PLTSP56215
- Mini Bi-Pin G5 base

APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	LED L70 Life Hours	Warranty
LEDT-10081	5000	3500	82	25	120-277	YES	Mini-Bi-Pin	≥100,000	5 Year

SPECIFICATIONS

DIMMABLE	NO	LUMENS	3,500
DLC LISTED	YES	VOLTAGE	120-277
SAFETY RATING	UL DAMP	LENS	FROSTED GLASS
CRI	82	BASE TYPE	Mini Bi-Pin
COLOR	DAYLIGHT WHITE	BALLAST TYPE	BALLAST BYPASS
COLOR TEMPERATURE	5000K	DIAMETER	0.74 IN.
LED L70 LIFE HOURS	≥100,000	LENGTH	45.79 IN.
WATTAGE	25 WATTS	FLUORESCENT EQUAL.....	54 WATT