LED
4 ft. Direct Wire T5 Tube

FEATURES

- Meets DLC performance and efficiency criteria
- Equivalent to a 54-Watt fluorescent tube
- Frosted glass lens to evenly diffuse light
- 5000 Kelvin daylight color temperature
- UL listed for use in damp locations
- DLC® Part Number: PLTSP56215
- Mini Bi-Pin G5 base

APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies

SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	Life Hours	Warranty
LEDT-10081	5000	3500	82	25	120-277	YES	Mini-Bi-Pin	50,000	5 Year

SPECIFICATIONS

DIMMABLE ..... NO
DLC LISTED ..... YES
SAFETY RATING ..... UL DAMP
CRI 82
COLOR ..... DAYLIGHT WHITE
COLOR TEMPERATURE 5000K
LIFE HOURS 50,000
WATTAGE ..... 25 WATTS

LUMENS 3,500
VOLTAGE 120-277
LENS ..... FROSTED GLASS
BASE TYPE ..... MINI BI-PIN
BALLAST TYPE ..... BALLAST BYPASS
DIAMETER ..... 0.74 IN.
LENGTH ..... 45.79 IN.
FLUORESCENT EQUAL..... 54 WATT