

# LED

## 4 ft. Double-Ended T8 Tube



### FEATURES

- Compatible with both shunted and non-shunted sockets
- Meets DLC performance and efficiency criteria
- Equivalent to a 32-Watt fluorescent T8 tube
- 4000 Kelvin cool white color temperature
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- DLC® Part Number: PLTSP32214
- Bi-Pin G13 base

### APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



| SKU#       | Kelvin | Lumens | CRI | Wattage | Voltage | DLC? | Base   | Life Hours | Warranty |
|------------|--------|--------|-----|---------|---------|------|--------|------------|----------|
| LEDT-10083 | 4000   | 1800   | 82  | 12      | 120-277 | YES  | Bi-Pin | 50,000     | 5 Year   |

### SPECIFICATIONS

|                         |            |                        |                |
|-------------------------|------------|------------------------|----------------|
| DIMMABLE .....          | NO         | LUMENS .....           | 1,800          |
| DLC LISTED .....        | YES        | VOLTAGE .....          | 120-277        |
| SAFETY RATING .....     | UL DAMP    | LENS .....             | FROSTED GLASS  |
| CRI .....               | 82         | BASE TYPE .....        | G13            |
| COLOR .....             | COOL WHITE | BALLAST TYPE .....     | BALLAST BYPASS |
| COLOR TEMPERATURE ..... | 4000K      | DIAMETER .....         | 0.98 IN.       |
| LIFE HOURS .....        | 50,000     | LENGTH .....           | 47.67 IN.      |
| WATTAGE .....           | 12 WATTS   | FLUORESCENT EQUAL..... | 32 WATT        |