



LED Recessed Retrofits

DIMMABLE • 35,000 HOURS • EASY INSTALLATION

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Industrial
- Retail
- Residential
- Healthcare

FEATURES

- Long life: 35,000 hours
- Very low heat generation
- Excellent color consistency and CRI
- Mounts directly to recessed can: 4 or 5/6 inch
- Shatter resistant
- Smooth, uniform dimming from 100 - 5%

BENEFITS

- Minimizes replacement and maintenance costs
- Perfect for sensitive display lighting such as art galleries
- Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
- Easy installation and integrated trim Pigtail and spring clips
- Lower the risk of injury and breakage

SPECIFICATIONS

| | |
|-----------------------------|-----------------------------------|
| Color Temperatures..... | 2700K, 3000K, 3500K, 4100K, 5000K |
| Wattage options | 14W, 11W, 10W, 9W |
| Input Line Voltage | 120 VAC |
| Input Line Frequency..... | 50/60HZ |
| Lamp Life (Rated) | 35,000 hours |
| Minimum Starting Temp | -22F/-30C |
| Maximum Operating Temp..... | 40°C |
| CRI..... | 80, 90 |

IC-rated for direct contact with insulation

UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.



5 YEAR WARRANTY
*Based on 12 hours use per day



RoHS COMPLIANT



LED

we know light.™





LED RECESSED RETROFITS

DIMMABLE • 35,000 HOURS • EASY INSTALLATION

| ITEM # | DESCRIPTION | ENERGY STAR V2.1 | VOLTAGE | LED WATTS | REPLACEMENT | LUMENS | LPW | CRI | COLOR TEMP | MOL (inches) | DIA (inches) | CASE QUANTITY |
|--------|-------------|------------------|---------|-----------|-------------|--------|-----|-----|------------|--------------|--------------|---------------|
|--------|-------------|------------------|---------|-----------|-------------|--------|-----|-----|------------|--------------|--------------|---------------|

5/6" Recessed Retrofits

120 Watt Replacement • 35,000 Hour

| | | | | | | | | | | | | |
|--------------|----------------------------------|---|------|----|-----|------|------|----|-------|-----|-----|---|
| LED14DR5627K | LED 5/6" 12W DIM 120W EQ - 2700K | ★ | 120V | 12 | 120 | 1250 | 89.3 | 80 | 2700K | 3.0 | 7.4 | 6 |
| LED14DR5630K | LED 5/6" 12W DIM 120W EQ - 3000K | ★ | 120V | 12 | 120 | 1300 | 92.9 | 80 | 3000K | 3.0 | 7.4 | 6 |
| LED14DR5641K | LED 5/6" 12W DIM 120W EQ - 4100K | ★ | 120V | 12 | 120 | 1300 | 92.9 | 80 | 4100K | 3.0 | 7.4 | 6 |
| LED14DR5650K | LED 5/6" 12W DIM 120W EQ - 5000K | ★ | 120V | 12 | 120 | 1350 | 96.4 | 80 | 5000K | 3.0 | 7.4 | 6 |

75 Watt Replacement • 35,000 Hour

| | | | | | | | | | | | | |
|--------------|----------------------------------|---|------|-----|----|-----|------|----|-------|-----|-----|---|
| LED11DR5627K | LED 5/6" 9.5W DIM 75W EQ - 2700K | ★ | 120V | 9.5 | 75 | 850 | 72.7 | 80 | 2700K | 3.0 | 7.4 | 6 |
| LED11DR5630K | LED 5/6" 9.5W DIM 75W EQ - 3000K | ★ | 120V | 9.5 | 75 | 850 | 77.3 | 80 | 3000K | 3.0 | 7.4 | 6 |
| LED11DR5641K | LED 5/6" 9.5W DIM 75W EQ - 4100K | ★ | 120V | 9.5 | 75 | 875 | 81.8 | 80 | 4100K | 3.0 | 7.4 | 6 |
| LED11DR5650K | LED 5/6" 9.5W DIM 75W EQ - 5000K | ★ | 120V | 9.5 | 75 | 900 | 86.4 | 80 | 5000K | 3.0 | 7.4 | 6 |

HiCRI • 65 Watt Replacement • 35,000 Hour

| | | | | | | | | | | | | |
|-------------------|---------------------------------------|---|------|----|----|-----|------|----|-------|-------|-----|---|
| L11DR56D3527K95** | LED 5/6" 11W HiCRI DIM 65W EQ - 2700K | ★ | 120V | 11 | 65 | 700 | 63.6 | 90 | 2700K | 3.125 | 7.4 | 6 |
| L11DR56D3530K95** | LED 5/6" 11W HiCRI DIM 65W EQ - 3000K | ★ | 120V | 11 | 65 | 750 | 86.2 | 90 | 3000K | 3.125 | 7.4 | 6 |

4" Recessed Retrofits

75 Watt Replacement • 35,000 Hour

| | | | | | | | | | | | | |
|-------------|-------------------------------|---|------|----|----|-----|------|----|-------|-----|-----|---|
| LED10DR427K | LED 4" 10W DIM 75W EQ - 2700K | ★ | 120V | 10 | 75 | 750 | 75.0 | 80 | 2700K | 3.0 | 5.0 | 6 |
| LED10DR430K | LED 4" 10W DIM 75W EQ - 3000K | ★ | 120V | 10 | 75 | 750 | 75.0 | 80 | 3000K | 3.0 | 5.0 | 6 |
| LED10DR435K | LED 4" 10W DIM 75W EQ - 3500K | | 120V | 10 | 75 | 620 | 62.0 | 80 | 3500K | 3.0 | 5.0 | 6 |
| LED10DR441K | LED 4" 10W DIM 75W EQ - 4100K | ★ | 120V | 10 | 75 | 800 | 80.0 | 80 | 4100K | 3.0 | 5.0 | 6 |
| LED10DR450K | LED 4" 10W DIM 75W EQ - 5000K | ★ | 120V | 10 | 75 | 800 | 80.0 | 80 | 5000K | 3.0 | 5.0 | 6 |

HiCRI • 50 Watt Replacement • 35,000 Hour

| | | | | | | | | | | | | |
|-----------------|------------------------------------|--|------|---|----|-----|------|----|-------|-----|-----|---|
| L9DR4D3527K95** | LED 4" 9W HiCRI DIM 50W EQ - 2700K | | 120V | 9 | 50 | 550 | 61.1 | 90 | 2700K | 3.0 | 5.2 | 6 |
| L9DR4D3530K95** | LED 4" 9W HiCRI DIM 50W EQ - 3000K | | 120V | 9 | 50 | 550 | 61.1 | 90 | 3000K | 3.0 | 5.2 | 6 |

* JA8 Compliant
+ All Plastic Body



*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcp.com

