PL H 15.5W BYP TITANIUM LED SERIES







PRO

- High output 1800lm
- Built-in universal voltage driver Bypass installation
- Ompatible with G24d, GX24d, G24q & GX24q sockets
- Exceptional efficacy 116 LPW
- U Lasts 4 times longer than CFL
- Available in 3000K, 3500K & 4000K CCT






















PL H 15.5W BYP TITANIUM LED SERIES









1.78"(45mm)

G24d, GX24d, G24q & GX24q (2/4-pin CFL) Base:

Voltage: 120-277V

Dimmable: No PF: 0.9

Lifetime (L70): 50,000 hrs Weight: 0.55lb / 249g



Note: This lamp may not fit in all 8" recessed cans. It is recommended a test installation be performed prior to the final installation.

SPECIFICATIONS

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
15.5PLH/830/BYP	98252	15.5	Warm White 3000K	82	1700	110	110°
15.5PLH/835/BYP	98253	15.5	Neutral White 3500K	82	1750	113	110°
15.5PLH/840/BYP	98254	15.5	Cool White 4000K	82	1800	116	110°

Suitable for damp locations. Not for use where directly exposed to weather or water * Not intended for use in enclosed fixtures